

# MERU

A statement in motion – modern, quiet, and powerful.

52"

- Matte Champagne / White • MERU-52-MCP-MWH-MTR
- Matte Black / Dark Brown • MERU-52-MBK-DB-MTR Matte
- Champagne / Dark Brown • MERU-52-MCP-DB-MTR Brushed
- Nickel / Black • MERU-52-BN-MBK-MTR



Matter-Enabled | ABS Blades

Remote Control | DC Motor | Outdoor Rated



## Product Details

**Airflow (CFM):** 5400 (High) -2000 (Low)

**Fan Control:** Remote Included

**No. of speeds:** 6 Speed

**Indoor/Outdoor:** Indoor / Outdoor (Covered Patio)

**Motor Type /Size:** DC

**Fan Size (in.)/Mounting Type:** 52" / Downrod, Flat or Angled ceiling (18° max)

**Housing:** Matte Champagne, Matte Black, or Brushed Nickel

**Blades:** Non-reversible, Matte Black, White or Dark Brown

**Lead Wire:** 54" Long with an additional Extension wire to allow 48-inch downrod (sold separately)

**Distance from ceiling to bottom of light kit once installed:** 13.8"

### Ceiling Fan Dimensions

| Mounting options: |                     |                              |                                             |
|-------------------|---------------------|------------------------------|---------------------------------------------|
| Flat Ceiling*     |                     | Slope* (Max.18°)             |                                             |
| Fan Size:<br>52"  | Blade Pitch:<br>13° | Downrod<br>Included:<br>6 in | Recommended Room Size:<br>Up to 350 sq. ft. |

#### Recommended Downrod Length per Ceiling Height

For maximum comfort, fan should be installed approximately 8 ft from the floor.

| Downrod Length |       | Ceiling Height |        |
|----------------|-------|----------------|--------|
| 1.83 m         | 72 in | 16 ft          | 4.88 m |
| 1.52 m         | 60 in | 15 ft          | 4.57 m |
| 1.22 m         | 48 in | 14 ft          | 4.27 m |
| 91.44 cm       | 36 in | 13 ft          | 3.96 m |
| 60.96 cm       | 24 in | 12 ft          | 3.66 m |
| 45.72 cm       | 18 in | 11 ft          | 3.35 m |
| 30.48 cm       | 12 in | 10 ft          | 3.05 m |

Compatible with any unthreaded 1.00 in dia downrod

## Application

