

VENTUS

Model: Ventus-52MWH/Ventus-60MWH
Ventus-52MBK/Ventus-60MBK
Ventus-52BNSLV/Ventus-60BNSLV



Brushed Nickel/Silver



Matte Black



Matte White



Key Features & Benefits

- ABS Blades with Solid Finishes and Sleek Minimalist Design
- DC Motor and ETL listed
- Lifetime motor warranty



SOFT WHITE (3000K)

BRIGHT WHITE (4000K)

DAYLIGHT (5000K)

Adjust color of light with
included remote control

Product Specifications

Fan Size in Inches

52"/ Downrod mount only, Flat or Angled ceiling (max. 18 degree)

60"/ Downrod mount only, Flat or Angled ceiling (max. 18 degree)

Lead Wire

12" standard coming from motor with quick connector. Additional 44" extension lead wires with quick connectors included to allow for a 48" downrod (sold separately)

No. of Blades/Blade Material
3/ABS

Light Kit (Y/N)

Y / (must be installed with Light kit)

CFM (High)

5663

6100

Blade Arms

N/A

Remote Control (Y/N)
Y

Lens Type

PC

Motor Type (AC, DC)/Size

DC / 156x8

DC / 156x12

Damp or Wet Rated

Dry Rated

Distance from ceiling to bottom of the light kit once installed: 12.72"

Type of Bulbs

LED Module
(can be replaced)

Indoor/Outdoor/Finish

Indoor Only

Reversible, Blade Finish

Non-Reversible
Available in Matte Black /
Matte White or Silver Finish

Distance from Ceiling to bottom of blade once installed: 11.08"

Bulb Wattage

18W (Dimmable)

For LED Only

Lumen Output (Raw/Fixture)
1314/1000

Lumens/Watt
56

Color Temperature / CRI
3000K/4000K/5000K/≥90

LED Chip Brand
BRIDGELUX

Driver Module
AC