

LED POST TOP



← Fitter section slips over 3" or 2 1/2" pole or tenon

Specifications and Features:

Radiant™ LED

- Conformal Coating LED Light Engine
- CCT: Standard-3000K, 4000K, & 5000K
- 2700K, Amber, LPS (1800K) Offered for Some Wattages - Consult Factory
- Static Colors Available - Contact Factory

Distribution

- Types II, III, IV, V

Electrical

- Electronic Driver, 120-277V, 50/60Hz or 347/480V, 50/60Hz
- 0-10v Dimmable Driver
- Standard Surge Protection Included (6kV Line-Line; 10k-V Line-Earth)

Controls (Optional)

- Button eye photo control (PC)

Housing

- Decorative cast aluminum capital with acrylic globe

Finish

- Super Durable Polyester Powder Coat Finish. Custom Finishes Available, Including Patinas and All RAL Colors.

Listings & Ratings

- ETL Listed to UL 1598 Standard for Wet Location and IP66.
- LED is IP66 Rate

Warranty

- 5 Year Limited Warranty

EPA: 2.1
Weight: 26 lbs (Max.)

Order Information Example:

AST2FA16PTP30W4KU3DEC1BK

ASTRIX 2

Model	Globe/Lens	Globe Size	Capital	Wattage	CCT	Voltage	Optics	Options	Finish
ASTRIX 2=Astrix 2	WA =White (Opal) Acrylic** WP =White (Opal) Polycarbonate*** FA =Frosted Acrylic FP =Frosted Polycarbonate PRSA =Prismatic Acrylic PRSP =Prismatic Polycarbonate* **18" & 20" Globe Only ***22" Globe Only, Type V Only ****Type V Only	10=10" 12=12" 14=14" 18=18" 20=20" 22=22"* *White Acrylic Only	C1 =PLC1 C2 =PLC2 C3 =PLC3 C4 =PLC4 C5 =PLC5 C6 =PLC6 C7 =PLC7 C8 =PLC8, C9 =PLC9 C10 =PLC10, C11 =PLC11 *Adder for C8, C10,C11	10W=10w 15W=15w 20W=20w 30W=30w	3K=3000K 4K=4000K 5K=5000K	U=120-277V H=347/480V	2=Type II 3=Type III 4=Type IV 5=Type V	PC =Button Eye Photo Control N =None	STANDARD FINISHES BK =Black BZ =Bronze DBZ =Dark Bronze WH =White GR =Green SM =Silver Metallic GY =Light Gray TBK =Textured Black CC =Custom Color (Consult Factory)

LED POST TOP

Photometric Data



6" Radiant™

RADIANT™ LED LIGHT ENGINE SPECIFICATIONS:

Lumen Output for Astrix 2					
Wattage (Catalog Logic)		10 Watts (10W)	15 Watts (15W)	20 Watts (20W)	30 Watts (30W)
Radiant Size (DIA.)		6"	6"	6"	6"
Input Watts		10.2	14.6	20.4	30.6
Optic	CCT	Delivered Lumens			
2 = Type II Clear, Prismatic or Frosted	3K	1,344	1,763	2,352	3,527
	4K	1,371	1,800	2,400	3,600
	5K	1,392	1,828	2,437	3,655
	BUG Rating	B0-U2-G1	B1-U2-G1	B1-U2-G1	B1-U2-G1
3 = Type III Clear, Prismatic or Frosted	3K	1,342	1,760	2,348	3,521
	4K	1,369	1,797	2,396	3,595
	5K	1,390	1,825	2,433	3,649
	BUG Rating	B1-U2-G1	B1-U2-G1	B1-U2-G1	B1-U2-G1
4 = Type IV Clear, Prismatic or Frosted	3K	1,312	1,721	2,296	3,443
	4K	1,339	1,758	2,343	3,515
	5K	1,359	1,784	2,379	3,569
	BUG Rating	B1-U2-G1	B1-U2-G1	B1-U2-G1	B1-U2-G1
5 = Type V Clear, Prismatic or Frosted	3K	1,373	1,801	2,402	3,603
	4K	1,401	1,839	2,452	3,678
	5K	1,423	1,867	2,489	3,734
	BUG Rating	B1-U2-G1	B1-U2-G1	B2-U2-G1	B2-U2-G1
5 = Type V with White Opal Lens	3K	964	1,446	1,928	2,893
	4K	984	1,477	1,969	2,953
	5K	999	1,499	1,998	2,998
	BUG Rating	B1-U3-G1	B1-U3-G1	B1-U3-G2	B1-U4-G2

Please refer to the fixture's IES file for detailed information. Subject to change.

LED POST TOP

Cage



PLC1 - 8 3/4" High



PLC2 - 10 13/16" High



PLC3 - 6 7/8" High



PLC4 - 7 13/16" High



PLC5 - 9 15/16" High



PLC6 - 8 1/16" High



PLC7 - 8 3/8" High



PLC8 - 11 3/8" High



PLC9 - 14 1/4" High



PLC10 - 10 1/4" High



PLC11 - 15" High



PLC12 - 12 3/4" High

Dimensions

