


RSA 1020

4" Aluminum Fluted and Smooth Round Poles



The Fluted and Smooth Round Aluminum poles are built from extruded fluted or smooth aluminum tubing and are offered as direct burial or with a high-strength die cast aluminum base and are available side drilled for arm mounted area lighting luminaires or with tenon mounts for flood and post top luminaires. Typical area lighting applications include retail centers, industrial parks, schools and universities, parks and pedestrian pathways and gathering spaces. Mounting heights to 10-16 feet for PARF fluted and 10-20 feet for PARS smooth can be used based on selected luminaire application.

Specifications and Features:

Pole Specifications:

The Pole Shaft is of Uniform Wall Thickness and is One-Piece Extruded 6063 Aluminum Alloy With T6 Temper, Available in 4" Diameter. Anchor Base is Die Cast From 356 Alloy Aluminum and is Heat Treated to a T6 Temper After Welding. Wall Thickness: 5mm (.196").

Finish:

Textured Architectural Black Powdercoat Finish, Baked to Ensure Maximum Paint Adhesion, Hardness and Durability.

Anchor Bolts:

Anchor Bolts are Included, Sized Based on Pole Data Charts for the Selected Pole Size.

Hand Hole:

Die Cast Aluminum Reinforced Hand Hole and Cover with Ground Screw.

Base Cover:

Poles are Provided with a Two-Piece Formed Aluminum Base Cover that is Easily Assembled and Fitted Over Pole Base.

Pole Length:


Poles are Available in Standard Lengths as Shown in the Order Matrix. Poles can be Custom Cut to Order. Consult Factory.

Mounting Options:


Available Side Drilled for 1 side, 2@180 Degrees, 3@90 Degrees or 4@90 Degrees, Includes UV-Stabilized Polycarbonate Top Cover (4" Only).

Poles May Also Be Ordered With 2 3/8" OD or 2 1/2" OD Tenons for Use With Post Top Decorative Luminaires, Flood/Area Slip Fitter Fixtures, or Any of a Wide Variety of Pole Top Mounting Accessories. Stainless Steel Hardware.

Tenon Sizes:



Drill Template:



Project Information:

Project Name:	Fixture Type:
Complete Catalog #:	Date:
Comments:	

Notes:

- Side Drilled poles include UV-stabilized polycarbonate pole cap.
- All poles include anchor bolts standard, consult dimension table for size based on pole dimensions.
- All poles include square 2-piece black base cover.



RSA 1020

4" Aluminum Fluted and Smooth Round Poles

Order Information Example: PARF420ABBP3					
		B			
Model	Shaft/Height/Style	Color	Pole Top Mounting	Drill Template	Options
RSA-F =Fluted Aluminum Extruded Pole RSA-S =Smooth Aluminum Extruded Pole	416AB =16" Anchor Base Pole* 422DB =22" Direct Burial Pole* *Fluted PARF Only 420AB =20" Anchor Base Pole** **Smooth PARS Only	B =Black	D1 =Drilled 1 Side D2 =Drilled 2 Sides at 180 D3 =Drilled 3 Sides at 90 D4 =Drilled 4 Sides P2 =2½ x 4"H Tenon P3 =2½ x 3"H Tenon N =No Pole Top Mounting	(Leave Blank) =Poles with P2 or P3 Tenon S =Standard Arm/Accessories D =Small Kitty Hawk Arm (KH25A) E =Large Kitty Hawk Arm (KH45A) C =Custom (Specify) N =No Template	(Leave Blank) =No Options LAB =Less Anchor Bolts (2) LBC =Less Base Cover (3)


Wind Loading and Dimensional Data:

Pole Description		80 MPH	90 MPH	100 MPH	110 MPH	120 MPH	130 MPH	140 MPH	150 MPH	160 MPH	170 MPH	180 MPH	200 MPH
Shaft Size & Wall Thickness	Mounting Height	Max EPA (SQ FT)	Max EPA (SQ FT)	Max EPA (SQ FT)	Max EPA (SQ FT)	Max EPA (SQ FT)	Max EPA (SQ FT)	Max EPA (SQ FT)	Max EPA (SQ FT)	Max EPA (SQ FT)	Max EPA (SQ FT)	Max EPA (SQ FT)	Max EPA (SQ FT)
RSA-F, RSA-S	12'	24.20	19.20	14.80	11.80	10.95	9.06	7.58	6.37	5.38	4.57	3.88	0.65
	14'	19.40	15.40	11.60	9.20	8.61	7.02	5.78	4.76	3.93	3.25	2.67	-
	16'	15.00	12.00	8.90	6.93	6.64	5.31	4.27	3.41	2.70	2.14	1.64	-
RSA	20'	8.00	6.00	4.50	3.45	3.31	2.71	2.12	1.70	1.20	0.55	-	-


- NOTES:**
1. Maximum EPA (Effective Projected Area) based on "C" Exposure.
 2. EPAs are approximate, specific to location and local codes. Consult engineer for specific application.
 3. Allowable EPA Weight Load (LBS): To determine maximum pole loading weight, multiply allowable EPA by 30 LBS.
Example: PARF 16" pole in 120 mph zone = 199.2 LBS (6.64 x 30)
 4. Variations from sizes above are available upon inquiry at the factory.
 5. Satisfactory performance of poles is dependent upon the pole being properly attached to a supporting foundation of adequate design.

Pole Data:


Anchor Base Pole



Shaft Base Size	Bolt Circle A	Base Size B	Base Thickness C	Anchor Bolt Size
RSAF4 & RSAS4	7 1/2"-8 1/2" (191-215mm)	8" (203mm)	3/4" (19mm)	5/8" x 18"




Pole Top Mounting:




4" Round Aluminum Pole Mounting Options (Order separately, field installed.)

Spoke Brackets: Bronze Finish, Spoke Bracket have 7" Arms. Fit 2 3/8" (P2) Tenons.

All PTSB Spoke Brackets are 9" high from the bottom edge to the top center of the cap




Single Spoke Bracket
PTSB1SZ




Twin Spoke Bracket,
90° Arms
PTSB290SZ




Twin Spoke Bracket,
180° Arms
PTSB2180SZ



Triple Spoke Bracket, 90° Arm
PTSB390SZ*




Triple Spoke Bracket, 120° Arms
PTSB3120SZ*




Quad Spoke Bracket, 90° Arms
PTSB490SZ*

*Non-stock item. Consult factory for lead time.

Tenon Adaptors: Fit 2 3/8" (P2) Tenons.




Retrofit Tenon Adaptor for
2 3/8" Tenons
PSRTNB




Pole Tenon Adaptor
PTASUNVZ

4" Vertical Tenon Pole Top Fitters: Black Finish




2 1/2" Single Round
Vertical Tenon (P2)
PSRA42B



2 1/2" Single Round
Vertical Tenon (P3)
PSRA43B


4" Decorative Aluminum Pole Mounting Options (Order separately, field installed.)

Dual Mounting Arm: Black Finish, Accepts 3" Diameter Fitters, Fits 3" Tenon



Dual Head Decorative Pole Arm
PADAB


Wall Mounting Bracket: Black Finish, Accepts 3" Diameter Fitters




Single Decorative Wall Mount Bracket
PWASAB

Wall Mounting Bracket:


Bases:



Wall Mount Bracket
PRSWMBZ



Wall Mount 90° Bracket
PRSWMB90Z
Wt lbs 4.5, EPA 0.3




PRA4CVB




PB24A4B

Replacement Parts (Order Separately, Field Installed)

PRA4CVB	Square Cover for 4" Pole, Black Finish
PB24A4B	Two-Piece Base for 4" Pole, Black Finish



PBR1



PBS1

RSA 1020

4" Aluminum Fluted and Smooth Round Poles

PB Series

Cast Aluminum Decorative Clamshell Bases

Decorative Clamshell Bases are designed to create a clean decorative look and cover pole base anchoring hardware. Two styles are available in matching finish to coordinate with pole selection.

Specifications and Features:

Clamshell Bases:


Die cast aluminum, Stainless Steel Hardware. PBR1 and PBS1 include sets of inserts that allow use on 4" round poles.

Finish:


Textured architectural powdercoat finish, baked to ensure maximum paint adhesion, hardness and durability.

Pole Fit:


Bases are designed to fit poles based on dimensions shown.



**Smooth Pole
4" Dia
PARS**



**Fluted Pole
4" Dia
PARF**



4" Round Inserts.

Order Information Example:

PBR1B

Model	Color
-------	-------

PBR1=Round Base
PBS1=Square Base

B=Black
P=Platinum (PBR1 Only)
Z=Bronze
C=Custom (Consult Factory)

Project Information:

Project Name:

Fixture Type:

Complete Catalog #:

Date:

Comments:

Notes: