

► Features

LED ufo highbay lights is a device which are consist of aluminum alloy frame, LED light source model and driver. It can be a replacement of HID and other traditional light fixture, provided with higher efficacy, a longer lifetime 50,000H at least or even more up to 100,000H and very lower breakdown opportunity, higher reliability and better cost than any light before. The high-performance, IP66-rated luminaire delivers a minimum of 150 lm/W, providing significant energy savings while remaining durable in the field.


- ☑ European and American design style, high quality aluminum die casting, Surfacepainting process, never fade, anti-cracking.
- ☑ Adopt aerodynamic design, take heat away quickly, keep low temperature for heat sink and LED chip for longer lifespan and higher light efficiency.
- ☑ A variety of installation ways, Suitable for Hook/Ring, Chain, Pole, Bracket and so on. All the screws are 304 stainless steel screws with stronger corrosion resistance ability
- ☑ Use branded led chip, high CRI, light efficiency up to 150 lm/W, low light decay and long lifespan.
- ☑ Through various of experimental tests: wind resistance level test, conduction radiation, 1.5G seismic test, UV aging test, drop, stacking test etc.
- ☑ 6KV anti-surge LED driver, installed on die casting cover of led driver, take heat away quickly to keep lower temperature and longer lifespan

► Dimensions


unit: mm/inch



Hook Mount




100W/150W




200W/250W

U-Bracket





100W/150W



200W/250W

U-Bracket
Hole spacing



DATA SHEET

Power	100W	150W	200W	250W
Model	GKD-100W-E13	GKD-150W-E13	GKD-200W-E13	GKD-250W-E13
Dimension(mm)	Ø 271xH154	Ø 271xH154	Ø 359xH161	Ø 359xH161
Luminous Flux	15000lm	22500lm	30000lm	37500lm
Power regulation	Each model supports 4 positions wattage regulation: 100%, 80%, 60%, 40%(Optional)			
Beam Angle	90°			
Materials	Aluminum alloy			
Luminous Efficacy	150lm/w			
Operation Temp	-40 to +50°C			
CCT	Adjustable CCT 3000K 4000K 5000K			<div style="display: flex; align-items: center;"> <div style="border: 1px solid black; padding: 2px; margin-right: 5px;">3000K</div> <div style="border: 1px solid black; padding: 2px; margin-right: 5px;">4000K</div> <div style="border: 1px solid black; padding: 2px;">5000K</div> </div>
CRI	80+			<div style="border: 1px solid black; padding: 2px; display: inline-block;">Wattage Adjustable</div>
Life Span	50,000 hours at 25°C			
Voltage	120-277VAC/50-60Hz 200-480VAC/50-60Hz Optional)			
Driver	UL listed power supply			
Dimming	Dimmable			
Color	Black/White/Dark			
Luminous Source	SMD LED 3030			
IP Rating	IP 65			
PF	>0.9			
Installation	Hook mount; U-Bracket mount; Conduit Pendant Mount			
Warranty	5 Years			

▶ ACCESSORIES (Optional)

					
Emergency Battery 25W 3500lm 90min, suit for 210W, 230W. 16W 2000lm 90min, suit for 100W, 150W, 160W	Plug-and-Play PIR Sensor PIR sensor: MSANT12VPH01 Bluetooth PIR sensor: MSANT12VPHB01	Plug-and-Play Microwave Sensor Microwave sensor: MSANT12VMH01 Bluetooth microwave sensor: MSANT12VMH01	U-Bracket Use for surface mount	Aluminum Reflector	Pc Reflector

Note: Main Stocking sensor's SKU: MSANT12VPH01

ORDERING GUIDE

Example: GKD-E13-(Wattage)-(voltage)-(CCT)-(Finish)-(Sensor)-(mounting)

Fixture Type	Wattage	Voltage	CCT	Finish	Sensor (Option)	Mounting	Internal Code
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
GKD-E13 High Bay Series	10 100W 15 150W 20 200W 25 250W	Blank 100V 100-277VAC 200V 200-480VAC	DDK Adjustable color temperature 30K' 3000K 40K' 4000K 50K' 5000K	Blank B Black W White D Dark Bronze	M With Sensor Blank Without Sensor	Blank Hook mount TR Trunnion Mount PD Conduit Pendant Mount	Blank Alphanumeric

► Emergency power supply(optional)

Emergency Battery
25W 3500lm 90min

Plug-and-Play Sensor (optional)
Sensor allows for security and energy saving.

Installation accessory
Available for both hook mount, conduit mount and surface mounting with U-bracket(optional).
U-bracket allows to adjust the direction to illuminate any area you need.

Transformer BOX
Transformer can be easily added into the Junction-box and convert to HV models, reducing SKUs and inventory pressure.

Housing
Rugged die-cast housing with corrosion-resistant powder coating for effective protection.

► CCT and power adjustment(optional)

CCT AND WATTAGE SELECTABLE

This fixture has the function of adjusting the lumens output and color temperature on-site.

CCT SELECT

3000K 4000K 5000K

Offer three CCT adjustable (3000K, 4000K, 5000K) or two CCT adjustable (4000K, 5000K)

WATTAGE SELECT

40% 60% 80% 100%

Each model supports 4 positions wattage regulation: 100%, 80%, 60%, 40%


LED HIGHBAY SERIES

▶ Application case


Parking area lighting/Workshop lighting/Warehouse lighting/indoor stadium lighting/Factories lighting



• Warehouse lighting



• Factories lighting



• Garage lighting

▶ MOUNTING



Hook Mount



Conduit Pendant Mount



U-Bracket Mount

▶ Packge info

Packaging	Carton Size(mm) (L*W*H)	N.W	G.W	Volume weight
1pc/CTN(100W/150W)	355x365x115	2.1kg	2.6kg	3.1kg
1pc/CTN(200W/250W)	405x365x115	2.8kg	3.4kg	3.6kg