

BAMBOO LIGHTING FIXTURE

INTRODUCTION

FEATURE

Elegance Design with Durable Quality Long Lifespan Design>50,000hours Working Temperature: -30 ℃~50 ℃

MATERIALS & FINISH

Frame: Environment-friendly Bamboo Shade: Environment-friendly Bamboo Lamp Holder: E26 Fitment INSTALLATION

According to models choosing.

STANDARD

Designed and Manufactured to Comply with TUV/CE/ROHS/GS/cUL Standard IP20 Protection, Class I Electrical

OPTION


LED Color Temperature: CCT2700~6000K

LED Lamp: E26 (MAXI.50W)

Dimension: [Unit: MM]







FC1000A: Φ1000/39.4" FC1200A: Ф1200/47.3" FC1500A: Φ1500/59"

CASE STUDY:







MODEL	NAME	INPUT [V]	FITMENT		DIEMENSION	REMARK
			TYPE	POWER	[INCH]	KLWAKK
GTF5821A-FC400A-MPW	Pendant	AC100~277V	1xE26	Maxi.1x50W		
GTF5821A-FC600A-MPW	Pendant	AC100~277V	1xE26	Maxi.1x50W		
GTF5821A-FC800A-MPW	Pendant	AC100~277V	1xE26	Maxi.1x50W		
GTF5821A-FC1000A-MPW	Pendant	AC100~277V	1xE26	Maxi.1x50W		
GTF5821A-FC1200A-MPW	Pendant	AC100~277V	1xE26	Maxi.1x50W		
GTF5821A-FC1500A-MPW	Pendant	AC100~277V	1xE26	Maxi.1x50W		

NOTE:

Tolerances of power and luminous flux are ±10%, tolerance of color rendering index is ±5.