


INTERIOR LIGHTING FIXTURE (Single Glass Ball)

INTRODUCTION



FEATURE

Elegance Design with Durable Quality
 Long Lifespan Design >50,000hours
 Working Temperature: -20°C~40°C

MATERIALS & FINISH

Frame: Painted Galvanized Steel
 Fitment: E26 (MAXI.50W)
 Shade: Blowing Glass
 [OPAL/PC]: Polycarbonate(PC)

INSTALLATION

Suspended

STANDARD

Designed and Manufactured to Comply with
 TUV/CE/ROHS/GS/cUL Standard
 IP20 Protection, Class I Electrical

OPTION

LED Bulb: 3~10W
 LED Color Temperature: CCT2700~6000K



CASE STUDY:



MODEL: [D-Ball Diameter]	NAME	INPUT [V]	FITMENT		DIEMENSION ΦxWxH [MM]	CANOPY LxWxH [MM]	SUSPENSION CORD	
			TYPE	POWER			RANGE	CUSTOM
GTF5613-201A-D150	Pendant Fixture	AC100~277V	1xE26	Maxi.50W	Φ150*H180	Φ120*H20	L10CM~200CM	
GTF5613-201A-D200	Pendant Fixture	AC100~277V	1xE26	Maxi.50W	Φ200*H230	Φ120*H20	L10CM~200CM	
GTF5613-201A-D250	Pendant Fixture	AC100~277V	1xE26	Maxi.50W	Φ250*H280	Φ120*H20	L10CM~200CM	
GTF5613-201A-D300	Pendant Fixture	AC100~277V	1xE26	Maxi.50W	Φ300*H330	Φ120*H20	L10CM~200CM	
GTF5613-201A-D350	Pendant Fixture	AC100~277V	1xE26	Maxi.50W	Φ350*H380	Φ120*H20	L10CM~200CM	
GTF5613-201A-D400	Pendant Fixture	AC100~277V	1xE26	Maxi.50W	Φ400*H430	Φ120*H20	L10CM~200CM	
GTF5613-201A-D500-OPAL/PC	Pendant Fixture	AC100~277V	1xE26	Maxi.50W	Φ500*H530	Φ120*H20	L10CM~200CM	
GTF5613-201A-D600-OPAL/PC	Pendant Fixture	AC100~277V	1xE26	Maxi.50W	Φ600*H630	Φ120*H20	L10CM~200CM	
GTF5613-201B-D150	Pendant Fixture	AC100~277V	1xE26	Maxi.50W	Φ150*H350	Φ120*H20	L10CM~200CM	
GTF5613-201B-D200	Pendant Fixture	AC100~277V	1xE26	Maxi.50W	Φ200*H400	Φ120*H20	L10CM~200CM	
GTF5613-201B-D250	Pendant Fixture	AC100~277V	1xE26	Maxi.50W	Φ250*H450	Φ120*H20	L10CM~200CM	
GTF5613-201C-D150	Pendant Fixture	AC100~277V	1xE26	Maxi.50W	Φ150*200*H500	Φ120*H20	L10CM~200CM	
GTF5613-201D-D150	Pendant Fixture	AC100~277V	1xE26	Maxi.50W	Φ150*300*H300	Φ120*H20	L10CM~200CM	
GTF5613-201E-D150	Pendant Fixture	AC100~277V	1xE26	Maxi.50W	Φ150*H180	Φ120*H20	L10CM~200CM	
GTF5613-201F-D150	Pendant Fixture	AC100~277V	1xE26	Maxi.50W	Φ150*H450	Φ120*H20	L10CM~200CM	
GTF5613-201G-2D150	Pendant Fixture	AC100~277V	1xE26	Maxi.50W	Φ150*200*H500	Φ120*H20	L10CM~200CM	
GTF5613-201H-D150	Pendant Fixture	AC100~277V	1xE26	Maxi.50W	Φ150*H250	Φ120*H20	/	
GTF5613-201H-D200	Pendant Fixture	AC100~277V	1xE26	Maxi.50W	Φ200*H300	Φ120*H20	/	
GTF5613-201H-D250	Pendant Fixture	AC100~277V	1xE26	Maxi.50W	Φ250*H350	Φ120*H20	/	
GTF5613-201J-D200	Pendant Fixture	AC100~277V	1xE26	Maxi.50W	Φ200*H1350	Φ120*H20	L130/100/70/40CM	
GTF5613-201J-D250	Pendant Fixture	AC100~277V	1xE26	Maxi.50W	Φ250*H1400	Φ120*H20	L135/105/75/45CM	

NOTE:

All parameters are measured at 25°C ambient temperature, 35% humidity experimental environment.
 Tolerances of power and luminous flux are ±10%, tolerance of color rendering index is ±5.

CIP Lighting

T: 1-803-766-0243

W: www.ciplighting.com

E: info@ciplighting.com