

PRODUCT SPECIFICATION

LIGHTING								
Series	LED ACOUSTIC LIGHT SERIES		Model	LL0403SAC				
				Project:				
				Type:				
				Notes:				
				Overview				
				Combining the elements of color, shape, and sound, this acoustic family is an extremely versatile lighting tool for a range of projects. Adopt 0.47"(12mm) ployster fiber in a range of color options. With great acoustic performance, has sound absorbing, non-toxic, non-allergeic and non-irritant characteristics. E26 base tube in side. And for simple design with Polyster fiber, easy to disassemble and install.				
Certificate				Features				
Intertek DAMP LOCATION TEARS TO HICHO TO				1. Easy to disasemble and installation 2. Permanent flame retardant ASTM E84 Class A 3. The material meet the requirement of EN717-1:2004 standards which are free of formaldehyde and environment friendly 4. Operation Voltage: AC120-277V, non-dimmable 5. 36 acoustic felt colors for optional 6. Efficiency: ≧70lm/w 7. NRC reach more than 0.8 base on 7.87"(200mm) air gap 8. Power: Advise max power not exceed 40W				
Туре	Suspended			Size				
280 (11.0") 1200 (47.2")			Model type		D	н	Dimension code	
			LL0403SAC		47.2"(1200mm)	11.0"(280mm)	D47H11	
Ordering Format	Model No. Installation		Acoustic Configuration			Dimension code	Acoustic Color	
	CIP-LL0403	s	suspended	AC	Асоц	ıstic with light	D47H11	Acoustic Color Code



technical information!

