

GEO

LED Well / Deck Light

Low-voltage in-ground well/deck light for decks, patios, pathways, and landscape borders. Available in a round (GEO-R) or square (GEO-S) housing — both include a 2.5" bottom cut-out for flush deck and wall mounting and an easy-install ground stake. The frosted lens delivers 360° warm-white uplighting; an optional snap-on cover (Silver finish) redirects it to focused 90°/180° side lighting.

- 150 lumens of 360° warm-white uplighting
- Optional snap-on cover for focused 90°/180° side lighting
- Choose round (GEO-R) or square (GEO-S) housing
- IP68 — fully sealed, wet-rated for in-ground use
- Rugged metal construction with frosted lens
- 2.5" bottom cut-out for deck/wall + ground stake included



IP68


LUMEN OUTPUT	150 lm	FINISH	Antique Brass, Silver
EFFICACY	83 lm/W	IP / IMPACT	IP68 · Wet Rated
COLOR TEMP / CCT	3000K	MATERIAL	Rugged metal · frosted lens
COLOR QUALITY / CRI	80 (Ra)	LENS	Frosted lens · opt. snap-on cover (Silver)
DISTRIBUTION	360° uplight · 90°/180° focused (opt.)	MOUNTING	Ground stake (incl.) · 2.5" deck/wall cut-out (both)
WATTAGE	1.8 W	CORD LENGTH	48" (no barrel connector)
VOLTAGE	12–15V AC	DIMENSIONS	Ø4.5" / 4.5" sq × 3.9" H (11.4 × 9.9 cm)

ILLUMINATION MODES

Standard frosted lens up-lights 360°; the optional snap-on cover (Silver) redirects to focused 90°/180° side lighting.



STD
360° Uplight
Frosted lens · warm white



SC
Directional · Round
Snap-on cover (Silver)



SC
Directional · Square
Snap-on cover (Silver)

Ordering & Dimensions

GEO

CONFIGURE YOUR PART NUMBER USING THE OPTIONS BELOW.

MODEL	SHAPE	CCT	OPTIONS	FINISH
GEO	R Round S Square	30 3000K	N None SC Snap-on directional cover*	AB Antique Brass SV Silver

* SC (snap-on directional cover — focused 90°/180° side lighting) is available with the Silver (SV) finish only.

Build Your Order Code — example values shown in grey

MODEL	SHAPE	CCT	OPTIONS	FINISH
GEO	R	30	N	AB

STANDARD FINISHES



AB
Antique Brass



SV
Silver

Dimensions

SHAPE	FACE SIZE	BEZEL HEIGHT	OVERALL DEPTH	CORD
Round (GEO-R)	Ø 4.5" (11.4 cm)	1.5" (3.8 cm)	3.9" (9.9 cm)	48"
Square (GEO-S)	4.5" sq (11.4 cm)	1.5" (3.8 cm)	3.9" (9.9 cm)	48"



Options

GEO

OPTICAL CONFIGURATION		MOUNTING		ELECTRICAL	
STD	360° uplight — frosted lens (standard)	ST	In-ground plastic stake — included	LV	12–15V AC low-voltage input
SC	Snap-on directional cover — focused 90°/180° side lighting (Silver finish only)	DW	Deck / wall mount — 2.5" bottom cut-out (both shapes)	CD	48" lead cord — no barrel connector



The frosted lens up-lights 360°; a slide-out plug and snap-on cover (Silver finish) redirect it to focused 90°/180° side lighting. A 2.5" bottom cut-out fits deck/wall mounting and an easy-install ground stake is included — on both the round (GEO-R) and square (GEO-S) housings.

Photometry

DELIVERED LUMENS

Optic	CCT	1.8W 1.8W
STD 360° Uplight	3000K	150

150 lm at 1.8W — 83 lm/W, 3000K, CRI 80 (Ra). The SC snap-on cover redirects the same output to focused 90°/180° side lighting; the factory publishes no separate figure for it. Photometric (IES) files on request.

DISTRIBUTION 360° uplight · 90°/180° focused (opt.) **EFFICACY** 83 lm/W **IES FILE** On request