




FEATURES:

- Aluminum Body
- Poly carbonate Cover
- Replaceable LED strips
- Isolated LED driver
- Easy maintenance

OPTIONS:

- Dimmable: TRIAC, 0/1-10V, DALI
- ON/OFF Switch
- Outlet socket
- USB socket
- Color: White, Silver, Black



MODEL NO.	WATTAGE	DIMENSION L * W * H(mm)	VOLTAGE	COLOR	CRI	LUMENS	BEAM ANGLE	WARRANTY
CIP-LED20-LPC	20W	578x86x75	100-277V 120-347V 220-240V	3000K 4000K 5000K 6500K	CRI>83 CRI>90	115Lm/W 140Lm/W	120°	5 years
CIP-LED220-LPC	40W	1188x86x75						
CIP-LED230-LPC	60W	1188x86x75						
CIP-LED225-LPC	50W	1474x86x75						
CIP-LED230-LPC	60W	1474x86x75						
CIP-LED240-LPC	80W	2369x86x75						
CIP-LED260-LPC	120W	2369x86x75						
CIP-LED20/20-LUPC	UP:20W DOWN:20W	578x86x75						
OG-LED10/20-LUPC	UP:10W DOWN:20W	578x86x75						
CIP-LED10/30-LUPC	UP:10W DOWN:30W	1188x86x75						
CIP-LED20/40-LUPC	UP:20W DOWN:40W	1188x86x75						
CIP-LED40/40-LUPC	UP:40W DOWN:40W	1188x86x75						
CIP-LED25/50-LUPC	UP:25W DOWN:50W	1474x86x75						
CIP-LED50/50-LUPC	UP:50W DOWN:50W	1474x86x75						
CIP-LED40/60-LUPC	UP:40W DOWN:60W	1474x86x75						
CIP-LED60/60-LUPC	UP:60W DOWN:60W	1474x86x75						
CIP-LED40/80-LUPC	UP:40W DOWN:80W	2369x86x75						
CIP-LED80/80-LUPC	UP:80W DOWN:80W	2369x86x75						
CIP-LED60/120-LUPC	UP:60W DOWN:120W	2369x86x75						




FEATURES:

- Aluminum Body
- Poly carbonate Cover
- Replaceable LED strips
- Built-in LED driver
- Easy maintenance

OPTIONS:

- Dimmable: TRIAC, 0/1-10V, DALI
- Color: White, Silver, Black
- 3-CCT turnable
- Wattage switchable
- Bluetooth remote control



MODEL NO.	WATTAGE	DIMENSION L * W * H(mm)	VOLTAGE	COLOR	CRI	LUMENS	BEAM ANGLE	WARRANTY
CIP-LED10/20-LUPC(2S)	UP:10W DOWN:20W	574x50x97	100-277V	3000K	CRI>83	115Lm/W	120°	5 years
CIP-LED20/40-LUPC(2S)	UP:20W DOWN:40W	1184x50x97		4000K				
CIP-LED25/50-LUPC(2S)	UP:25W DOWN:50W	1184x50x97	120-347V	5000K	CRI>90	140Lm/W		
CIP-LED40/60-LUPC(2)	UP:40W DOWN:60W	1470x50x97	220-240V	6500K				
CIP-LED40/80-LUPC(2S)	UP:40W DOWN:80W	2364x50x97						




FEATURES:

- Aluminum Body
- Poly carbonate Cover
- Replaceable LED strips
- Isolated LED driver
- 5 years warranty
- 100-277V/120-347V/220-240V 50-60Hz
- Easy maintenance
- CRI > 83, CRI > 90

OPTIONS:

- 2FT/3FT/4FT/5FT/6FT/8FT
- CCT 3000K/4000K/5000K/6500K
- Dimmable: TRIAC, 0/1-10V, DALI
- Microwave motion sensor
- Emergency battery back up
- Color: White, Silver, Black



MODEL NO.	WATTAGE	DIMENSION L * W * H(mm)	VOLTAGE	COLOR	CRI	LUMENS	BEAM ANGLE	WARRANTY
CIP-LED20-LPC(S)	20W	578X86X75	100-277V 120-347V 220-240V	3000K 4000K 5000K 6500K	CRI>83 CRI>90	115Lm/W 140Lm/W	120°	5 years
CIP-LED220-LPC(S)	40W	1188X86X75						
CIP-LED230-LPC(S)	60W	1188X86X75						
CIP-LED225-LPC(S)	50W	1474X86X75						
CIP-LED230-LPC(S)	60W	1474X86X75						
CIP-LED240-LPC(S)	80W	2369x86x75						
CIP-LED260-LPC(S)	120W	2369x86x75						
CIP-LED20/20-LUPC(S)	UP:20W DOWN:20W	578x86x75						
CIP-LED10/20-LUPC(S)	UP:10W DOWN:20W	578x86x75						
CIP-LED10/30-LUPC(S)	UP:10W DOWN:30W	1188x86x75						
CIP-LED20/40-LUPC(S)	UP:20W DOWN:40W	1188x86x75						
CIP-LED40/40-LUPC(S)	UP:40W DOWN:40W	1188x86x75						
CIP-LED25/50-LUPC(S)	UP:25W DOWN:50W	1474x86x75						
CIP-LED50/50-LUPC(S)	UP:50W DOWN:50W	1474x86x75						
CIP-LED40/60-LUPC(S)	UP:40W DOWN:60W	1474x86x75						
CIP-LED60/60-LUPC(S)	UP:60W DOWN:60W	1474x86x75						
CIP-LED40/80-LUPC(S)	UP:40W DOWN:80W	2339x86x75						
CIP-LED80/80-LUPC(S)	UP:80W DOWN:80W	2369x86x75						
CIP-LED60/120-LUPC(S)	UP:60W DOWN:120W	2369x86x75						