








Series	LED ACOUSTIC LIGHT SERIES		Model	CIP-LL0406SAC			
			Project:				
			Type:				
			Notes:				
			Overview				
			<p>Combining the elements of color, shape, and sound, this acoustic family is an extremely versatile lighting tool for a range of projects. Adopt 0.35"(9 mm) polyester fiber in a range of color options. With great acoustic performance, has sound absorbing, non-toxic, non-allergenic and non-irritant characteristics. E26 base tube in side. And for simple design with Polyester fiber, easy to disassemble and install.</p>				
Certificate			Features				
     			<ol style="list-style-type: none"> E26 base for LED bulb, easy to install and replace; Advise max power not exceed 40W Permanent flame retardant ASTM E84 Class A The material meet the requirement of EN717-1:2004 standards which are free of formaldehyde and environment friendly Operation Voltage: AC120-277V, non-dimmable 38 acoustic felt colors for option Efficiency: $\geq 70\text{lm/w}$ NRC reach more than 0.8 base on 7.87"(200mm) air gap 				
Type	Suspended		Size				
			Model type	D	H	Dimension code	
			CIP-LL0406SAC	17.8"(450mm)	11.8"(300mm)	D18H12	
Ordering Format	Model No.	Installation		Acoustic Configuration		Dimension code	Acoustic Color
	CIP-LL0406	S	Suspended	AC	Acoustic with light	D18H12	Acoustic Color Code

Acoustic Color Code								
	NSAC-001 141	NSAC-002 122	NSAC-003 120	NSAC-004 123	NSAC-025 138	NSAC-031 108	NSAC-029 112	NSAC-024 117
	NSAC-005 107	NSAC-006 106	NSAC-007 145	NSAC-008 129	NSAC-042 146	NSAC-043 115	NSAC-044 114	NSAC-028 110
NSAC-009 140	NSAC-019 126	NSAC-011 135	NSAC-012 133	NSAC-033 103	NSAC-034 102	NSAC-035 101	NSAC-036 105	
NSAC-013 111	NSAC-014 144	NSAC-021 130	NSAC-016 104	NSAC-038 127	NSAC-039 143	NSAC-040 124	NSAC-057 132	
NSAC-017 147	NSAC-018 125	NSAC-022 119	NSAC-020 128	NSAC-056 131	NSAC-055 142			

Order Example:	CIP-LL0406SAC-D18H12-NSAC-001 141
-----------------------	-----------------------------------

Light distribution	Optical system																																																			
<p>C0/C180</p> <p>90°</p> <p>60°</p> <p>45°</p> <p>106.6</p> <p>213.1</p> <p>319.7</p> <p>426.2</p> <p>532.8</p> <p>cd</p>	<table border="1"> <thead> <tr> <th>Height</th> <th>Center lx</th> <th>Diameter</th> </tr> </thead> <tbody> <tr><td>1.m</td><td>530.08 lx</td><td>312.13cm</td></tr> <tr><td>2.m</td><td>132.52 lx</td><td>624.26cm</td></tr> <tr><td>3.m</td><td>58.90 lx</td><td>936.39cm</td></tr> <tr><td>4.m</td><td>33.13 lx</td><td>1248.52cm</td></tr> <tr><td>5.m</td><td>21.20 lx</td><td>1560.65cm</td></tr> <tr><td>6.m</td><td>14.72 lx</td><td>1872.78cm</td></tr> <tr><td>7.m</td><td>10.82 lx</td><td>2184.92cm</td></tr> <tr><td>8.m</td><td>8.28 lx</td><td>2497.05cm</td></tr> <tr><td>9.m</td><td>6.54 lx</td><td>2809.18cm</td></tr> <tr><td>10.m</td><td>5.30 lx</td><td>3121.31cm</td></tr> <tr><td>11.m</td><td>4.38 lx</td><td>3433.44cm</td></tr> <tr><td>12.m</td><td>3.68 lx</td><td>3745.57cm</td></tr> <tr><td>13.m</td><td>3.14 lx</td><td>4057.70cm</td></tr> <tr><td>14.m</td><td>2.70 lx</td><td>4369.83cm</td></tr> <tr><td>15.m</td><td>2.36 lx</td><td>4681.96cm</td></tr> <tr><td>16.m</td><td>2.07 lx</td><td>4994.09cm</td></tr> </tbody> </table>	Height	Center lx	Diameter	1.m	530.08 lx	312.13cm	2.m	132.52 lx	624.26cm	3.m	58.90 lx	936.39cm	4.m	33.13 lx	1248.52cm	5.m	21.20 lx	1560.65cm	6.m	14.72 lx	1872.78cm	7.m	10.82 lx	2184.92cm	8.m	8.28 lx	2497.05cm	9.m	6.54 lx	2809.18cm	10.m	5.30 lx	3121.31cm	11.m	4.38 lx	3433.44cm	12.m	3.68 lx	3745.57cm	13.m	3.14 lx	4057.70cm	14.m	2.70 lx	4369.83cm	15.m	2.36 lx	4681.96cm	16.m	2.07 lx	4994.09cm
Height	Center lx	Diameter																																																		
1.m	530.08 lx	312.13cm																																																		
2.m	132.52 lx	624.26cm																																																		
3.m	58.90 lx	936.39cm																																																		
4.m	33.13 lx	1248.52cm																																																		
5.m	21.20 lx	1560.65cm																																																		
6.m	14.72 lx	1872.78cm																																																		
7.m	10.82 lx	2184.92cm																																																		
8.m	8.28 lx	2497.05cm																																																		
9.m	6.54 lx	2809.18cm																																																		
10.m	5.30 lx	3121.31cm																																																		
11.m	4.38 lx	3433.44cm																																																		
12.m	3.68 lx	3745.57cm																																																		
13.m	3.14 lx	4057.70cm																																																		
14.m	2.70 lx	4369.83cm																																																		
15.m	2.36 lx	4681.96cm																																																		
16.m	2.07 lx	4994.09cm																																																		

Material

Acoustic Shade	0.35"(9 mm) Polyester fiber
-----------------------	-----------------------------

<p>We reserve the right to make any design changes for continuous improvement without notification, contact us for the latest technical information!</p>	File name	NS/SS-LL0406SAC-REV2.0
--	------------------	-------------------------------