



FEATURES:

- 0.8mm steel housing
- 1.2mm aluminum heatsink
- Poly carbonate Cover
- Replaceable LED strips
- Isolated LED driver
- Easy maintenance

OPTIONS:

- Dimmable: TRIAC, 0/1-10V, DALI
- Microwave motion sensor
- Emergency battery back up
- Color: White, Silver, Black



| MODEL NO. | WATTAGE | DIMENSION L * W * H(mm) | VOLTAGE | COLOR | CRI | LUMENS | BEAM ANGLE | WARRANTY |
|--------------|---------|----------------------------|----------------------------------|----------------------------------|------------------|--------------------|---------------|----------|
| CIP-PLED-420 | 80W | 615x285x100 | 100-277V 120-347V 220-240V | 3000K 4000K 5000K 6500K | CRI>83 CRI>90 | 115Lm/W 140Lm/W | 120° | 5 years |
| CIP-PLED-620 | 120W | 615x410x100 | | | | | | |
| CIP-PLED-420 | 80W | 1225x285x100 | | | | | | |
| CIP-PLED-430 | 120W | 1225x285x100 | | | | | | |
| CIP-PLED-440 | 160W | 1225x285x100 | | | | | | |
| CIP-PLED-450 | 200W | 1505x285x100 | | | | | | |
| CIP-PLED-620 | 120W | 1225x410x100 | | | | | | |
| CIP-PLED-630 | 180W | 1225x410x100 | | | | | | |
| CIP-PLED-640 | 240W | 1225x410x100 | | | | | | |
| CIP-PLED-650 | 300W | 1505x410x100 | | | | | | |