

GTG1113A: LED BULKHEAD LIGHT

--	--	--	--	--	--

INTRODUCTION

FEATURE

Durable Optimized LED Lighting
 Long Lifespan >50,000hours
 Working Temperature: -30°C~50°C

MAIN MATERIAL

LED Brand: GUBO
 Driver Brand: GUBO
 Housing: Die-casted Aluminum
 Diffuser: Anti-UV Opal PC Diffuser

INSTALLATION

Surface Mounted: Ceiling, Wall, Pillar-top
 Suitable for Architecture Illumination, Like Balcony, Veranda, External Wall...

STANDARD

Designed and Manufactured to Comply with
 TUV/CB/CE/RoHS/SA/Erp/cETL/FCC
 IP65 Protection, Class I Electrical

CUSTOM OPTION

LED CCT: 1,800K~10,000K/R/G/B/Y
 [CRI]: [E] RA80, [G] RA90, [H] RA97
 [FJP]: Mounting Plate on Outlet Box
 [CSMD]: Bi-level Daylight Harvest Microwave Sensor
 F1: Custom Housing Finish Colors by RAL Code

WHITE RAL9010P	BLACK RAL9005P	DARK GREY RAL7016P	GREY RAL7043P	PEARL GREY RAL9022P
-------------------	-------------------	-----------------------	------------------	------------------------



MODEL	POWER [W]	LED TYPE	CCT [K]	CRI	FLUX [LM]	POWER FACTOR	BEAM ANGLE	CUSTOM DIMMING	INPUT [V]
GTG1113A-MSB165A	12W [6W]	48x0.5W SMD2835	G2700K	RA90	1110	>0.9	180°	[CDN]:Non-dimmable [CDT]:TRIAC(10%) [CDV]:0/1~10V(8%) [CDV0]:0~10V(1%) [CDV1]:1~10V(10%) [CDA]:DALI(1%) [+CDP]:PWM(1%)	
			G3000K	RA90	1180				
			G3500K	RA90	1180				
			G4000K	RA90	1270				
			G5000K	RA90	1270				
			G5700K	RA90	1270				
			G6500K	RA90	1240				
2C@12W	TWG	G2700K G6500K	RA90	1110	>0.9				
3C@12W	RGB	620nm 520nm 460nm	\	820	>0.9				
4C@12W	RGBW	620nm 520nm 460nm G2700K	\	1110	>0.9				
5C@12W	RGBTW	620nm 520nm 460nm G2700K G6500K	\	1110	>0.9				
GTG1113A-MRB260A MRB260B	18W [10W]	72x0.5W SMD2835	G2700K	RA90	1540	>0.9	180°	Following by Remote Driver [CDX]:DMX512(1%) [CRZ]:ZIGBEE(1%) [CRF]:2.4G RF(1%) [CRB]:Bluetooth(1%) [CDS]:SPI(1%)	AC100~277V [AC220~240V] [AC110~130V] [AC100~240V] [AC100~347V] 50/60Hz [CV DC12V] [CV DC24V] [CV DC42V]
			G3000K	RA90	1630				
			G3500K	RA90	1630				
			G4000K	RA90	1770				
			G5000K	RA90	1770				
			G5700K	RA90	1770				
			G6500K	RA90	1720				
2C@18W	TWG	G2700K G6500K	RA90	1540	>0.9				
3C@18W	RGB	620nm 520nm 460nm	\	1100	>0.9				
4C@18W	RGBW	620nm 520nm 460nm G2700K	\	1540	>0.9				
5C@18W	RGBTW	620nm 520nm 460nm G2700K G6500K	\	1540	>0.9				
GTG1113A-MRB300A MRB300B	30W [20W] [12W]	120x0.5W SMD2835	G2700K	RA90	2600	>0.9	180°	Following [Sensor] [CSL]: Photocell Lux Sensor [CSM]: Micro Motion Sensor [CSMD]: Bi-level Microwave Motion Sensor	
			G3000K	RA90	2740				
			G3500K	RA90	2740				
			G4000K	RA90	2960				
			G5000K	RA90	2960				
			G5700K	RA90	2960				
			G6500K	RA90	2890				
2C@30W	TWG	G2700K G6500K	RA90	2600	>0.9				
3C@30W	RGB	620nm 520nm 460nm	\	1900	>0.9				
4C@30W	RGBW	620nm 520nm 460nm G2700K	\	2600	>0.9				
5C@30W	RGBTW	620nm 520nm 460nm G2700K G6500K	\	2600	>0.9				

NOTE:

All parameters are measured at 25°C ambient temperature, 35% humidity experimental environment.
 Tolerances of power and luminous flux are ±10%, tolerance of color rendering index is ±5.

[FFS] Flush Surface Mounted Light

DIMENSION: [UNIT: MM]

NOTES:

Custom Installation and Accessories Referred to Another Catalogue of Fixing Kits.

CASE STUDY:

