

INTRODUCTION

FEATURE

Upgrade Classic Post Top Area Lighting
Long Lifespan >50,000hours
Working Temperature: -30°C~50°C

MAIN MATERIAL

LED Brand: GUBO
Module: Die-casted Aluminum
Driver Brand: GUBO
Housing: Die-casted Aluminum
Optics: High Efficiency PC Lens
(DB/EB): Dome Clear PC Diffuser

INSTALLATION

Installation: Post-Top Mount
[FSC]: Circular Pole Slipfitter
[MSTC]: Circular Tenon Spigot
Suitable for Road Light, like Street, Park.....

STANDARD

Designed and Manufactured to Comply with
CE/RoHS/CB/cETL/SAA Standard
IP65 Protection, Class I Electric

OPTION

LED CCT: 1,800K~10,000K/R/G/B/A
[CRI]: [E] RA80, [G] RA90, [H] RA97
[Pole]: Height 3M/3.5M/4.5M/6M/8M
Custom Housing Finish: Colors by RAL Code

WHITE	BLACK	GREY	DARK GREY
RAL9010P	RAL9005P	RAL7042P	RAL7016P

CASE STUDY:



100-277V	WARRANTY	SMD	30/60/90/120° T2/T3/T4/T5	IP65	IK08	EURO	USA.CA
[EB-FPC] CATENARY		(F-MC400A)		(F-MC600A)			



(C-MC560A)	(C-MC560B)	(E-MC620A)	(E-MC620B)	(G-MC700B)
------------	------------	------------	------------	------------



DIMENSION: [UNIT: MM]			
(C-MC350A)	(C-MC560A)	(C-MC560B)	(G-MC700A)
Discontinued	[MSTC34A]:Φ34	[MSTC34A]:Φ34	[MSTC40A]:Φ40
	325	370	800
	C-MC560A:Φ560	C-MC560B:Φ560	(G-MC700B): Φ700
(E-MC620A)	(E-MC620B)	(F-MC400A)	(F-MC600A)
[MSTC20A]:Φ20	[MSTC20A]:Φ20	[MSTC34A]:Φ34	[MSTC40A]:Φ40
[MSTC40A]:Φ40	[MSTC40A]:Φ40	381	[MSTC50A]:Φ50
375	705	(F-MC400A):Φ406	560
E-MC620A:Φ620	(E-MC620B):Φ620		(F-MC600A): Φ600

MODEL	POWER 【W】	LED TYPE	CCT 【K】	CRI	FLUX 【LM】	POWER FACTOR	BEAM ANGLE	OPTIONAL DIMMING	INPUT 【V】	
Discontinued							[Asymmetric] T2M:V90xH145° T3M:V110xH145° T4M:V120xH145°	[CDT]:TRIAC(15%) [CDV]:0/1~10V(8%) [CDV0]:0~10V(1%) [CDV1]:1~10V(15%) [CDX]:DMX512(1%) [CDA]:DALI(1%) [CDP]:PWM(1%)	AC100~277V [AC100~240V] [AC100~347V] [AC180~528V] 50/60Hz	
BELL 25-C-MC560A BELL-C-MC560B	40W [30W]	96x2W SMD3030	G2700K	RA90	3600	>0.9				
			G3000K	RA90	3790					
			G4000K	RA90	4020					
			G6500K	RA90	4020					
BELL-E-MC620A BELL-E-MC620B	60W	96x2W SMD3030	G2700K	RA90	5280	>0.9				
			G3000K	RA90	5560					
			G4000K	RA90	5900					
			G6500K	RA90	5900					
BELL-F-MC400A	80W	96x2W SMD3030	G2700K	RA90	7200	>0.9				[Symmetric] BL30D:30° BL60D:60° BL90D:90° BL120D:120° T5: 150°
G3000K			RA90	7580						
G4000K			RA90	8040						
G6500K			RA90	8040						
BELL-G-MC700B	80W	96x2W SMD3030	G3000K	RA90	7580	>0.9	[CV DC24V] [CV DC48V]			
G3000K			RA90	7580						
G4000K			RA90	8040						
G6500K			RA90	8040						
BELL-F-MC600A	80W	96x2W SMD3030	G3000K	RA90	9100	>0.9				
			G4000K	RA90	9660					
			G6500K	RA90	9660					
			G2700K	RA90	11450					
	100W	144x2W SMD3030	G3000K	RA90	12350	>0.9				
			G3500K	RA90	12350					
			G4000K	RA90	13230					
			G6500K	RA90	13230					

NOTE:

All parameters are measured at 25°C ambient temperature, 35% humidity experimental environment.
Tolerances of power and luminous flux are ±10%, tolerance of color rendering index is ±5.