

HECTOR

Ceiling Fixtures, Pendant

Features

Housing

Die-formed Cold-rolled Steel and Aluminum Extrusion
Finish Option: -06 White, -60 Brushed Aluminum, -05 Black

Electrical

High Power Factor, Low THD

Lamp

Built-in Module (Color Temperature Option – 3000K, 4000K)
LED: High Efficiency, High CRI, Binned and Mixed to Reach Uniform Light

Certification

ETL/cETL Listed, Suitable for Damp Locations

Warranty

5 Years Warranty on Driver and LED Module



LED Type

Model	Input Voltage	Input Wattage	CRI	Lumen (TYP)	CT	Finish	Shade	Dimension (OD X H x H1)	Energy Star
HECTOR 5048-xxxxK-05	120V-277V	17W	> 80	1600	3000K or 4000K	Black	Clear Glass	6.0" x 9.0"	---
HECTOR 4048-xxxxK-05	120V-277V	14W	> 80	1200	3000K or 4000K	Black	Clear Glass	4.8" x 7.8"	---
HECTOR 5048P-xxxxK-05	120V-277V	17W	> 80	1600	3000K or 4000K	Black	Clear Glass	6.0" x 9.1" x 6.0'	---
HECTOR 4048P-xxxxK-05	120V-277V	14W	> 80	1200	3000K or 4000K	Black	Clear Glass	4.8" x 7.8" x 6.0'	---

H1: 6', Hanging Cable Length ,Adjustable