



Min Bending Diameter



Cross Section(mm)

Cable Option

Integrated End Cap (IP68)




Front Entry





Closed End Cap


Accessories




Aluminium Profile
(1m/2m/3m)



Aluminium Mounting Clips
(2cm)



PC Profile
(1m/2m/3m)



Single Color

CIP - 2835 N P H W 8 - 12x20mm 10W - 12024(C) - W/R/G/B/Y/O/P

CCT	Power(W)	Efficiency (LM/W)	Lumen (LM/M)	Cutting Unit (mm)	Max. Run Length(M) CV	CC
2400K	10	29	290	50	5	15
2600K	10	24.2	242	50	5	15
3000K	10	28.5	285	50	5	15
4200K	10	27.2	272	50	5	15
6000K	10	28.1	281	50	5	15
Red	10	13.9	139	50	5	15
Green	10	27.5	275	50	5	15
Blue	10	5.4	54	50	5	15
Yellow	10	11.3	113	50	5	15
Orange	10	12.2	122	50	5	15
Pink	10	24.2	242	50	5	15

CCT Tunable

CIP - 2835 N P H W 8 - 12x20mm 10W - 19224 - (27-60K)

CCT	Power(W)	Efficiency (LM/W)	Lumen (LM/M)	Cutting Unit (mm)	Max. Run Length (M)
2700K	5	28	140	62.5	5
6000K	5	29	145	62.5	5
2700K+6000K	10	28.5	285	62.5	5

RGB

CIP - 5050 N P H W 8 - 12x20mm 10W - 8424 - RGB

CCT	Power(W)	Efficiency (LM/W)	Lumen (LM/M)	Cutting Unit (mm)	Max. Run Length (M)
R	3.3	11	36	83.3	5
G	3.3	39.3	130	83.3	5
B	3.3	7.4	24	83.3	5
RGB	10	19	190	83.3	5

RGB Pixel

CIP - 5050 N P H W 8 - 12x20mm 11.5W - 8024I - RGB

CCT	Power(W)	Efficiency (LM/W)	Lumen (LM/M)	Cutting Unit (mm)	Max. Run Length (M)	Protocol
R	4.8	4.57	22	125	5	SPI
G	4.8	14.9	70	125	5	
B	4.8	2.6	12	125	5	
RGB	11.5	8.9	99	125	5	

Note: CV=Constant Voltage CC=Constant Current