PRODUCT SPECIFICATION										
Series	LED ACOUSTIC LIGHT SERIES			Model CIP-LL0404SAC						
				Project:						
				Туре:						
				Notes:						
				Overview						
				Combining the elements of color, shape, and sound, this acoustic family is an extremely versatile lighting tool for a range of projects. Adopt 0.47"(12mm) ployster fiber in a range of color options. With great acoustic performance, has sound absorbing, non-toxic, non-allergeic and non-irritant characteristics. E26 base tube in side. And for simple design with Polyster fiber, easy to disassemble and install.						
Certificate	Sertificate				Features					
EO Intertek Intertek Intertek Intertek Intertek Intertek Intertek				 E26 base for LED bulb,easy to install and replace; Advise max power not exceed 40W Permanent flame retardant ASTM E84 Class A The material meet the requirement of EN717-1:2004 standards which are free of formaldehyde and environment friendly Operation Voltage:AC120-277V,non-dimmable 38 acoustic felt colors for option Efficiency: ≥ 70lm/w NRC reach more than 0.8 base on 7.87"(200mm) air gap 						
Type Suspended			Size							
			Model type		L	w	н	Dimension code		
507(20")			CIP-LL0404SAC		20"(507mm)	20"(507mm)	15.2"(387mm)	L20		
Ordering Format	Model No.	del No. Installation		Acoustic Configuration			Dimension code	Acoustic Color		
	CIP-LL0404	S	Suspended	AC Acous		stic with light	L20	Acoustic Color Code		

