



Min Bending Diameter



Cross Section(mm)

Cable Option

Integrated End Cap (IP68)



Front Entry





Closed End Cap


Accessories




Aluminium Profile
(1m/2m/3m)



Aluminium Mounting Clips
(2cm)



PC Profile
(1m/2m/3m)



Single Color

CIP - 2835 N P V W 8 - 16x15mm 10W - 12024(C) - W/R/G/B/Y/O/P

CCT	Power(W)	Efficiency (LM/W)	Lumen (LM/M)	Cutting Unit (mm)	Max. Run Length(M) CV	CC
2400K	10	37	370	50	5	15
2600K	10	37	370	50	5	15
3000K	10	37.5	375	50	5	15
4000K	10	41	410	50	5	15
6100K	10	37.5	375	50	5	15
Red	10	17.4	174	50	5	15
Green	10	48.9	489	50	5	15
Blue	10	8.9	89	50	5	15
Yellow	10	17.8	178	50	5	15
Orange	10	18.4	184	50	5	15
Pink	10	43.7	437	50	5	15

CCT Tunable

CIP - 2835 N P V W 8 - 16x15mm 10W - 16824 - (27-60K)

CCT	Power(W)	Efficiency (LM/W)	Lumen (LM/M)	Cutting Unit (mm)	Max. Run Length (M)
2700K	5	40	200	62.5	5
6000K	5	42	210	62.5	5
2700K+6000K	10	41	410	62.5	5

RGB

CIP - 5050 N P V W 8 - 16x15mm 10W - 8424 - RGB

CCT	Power(W)	Efficiency (LM/W)	Lumen (LM/M)	Cutting Unit (mm)	Max. Run Length (M)
R	3.3	16.5	54.45	83.3	5
G	3.3	61	201.3	83.3	5
B	3.3	12	39.6	83.3	5
RGB	10	29.5	295	83.3	5

RGB Pixel

CIP - 5050 N P V W 8 - 16x15mm 11.5W - 8424I - RGB

CCT	Power(W)	Efficiency (LM/W)	Lumen (LM/M)	Cutting Unit (mm)	Max. Run Length (M)	Protocol
R	4.8	4.57	22	125	5	SPI
G	4.8	14.9	70	125	5	
B	4.8	2.6	12	125	5	
RGB	11.5	8.9	99	125	5	