

PASCAL

Zoomable Track Head

A zoomable LED track head for H-type track. The beam adjusts from 10° to 60° on the fixture itself, so one head covers both accent and wash duties, and it rotates 350° with a 90° pivot. Three wattages — 15W, 30W and 45W — each with its own body size, on a CREE COB source. Order a fixed color temperature in Ra83 or Ra95, or a field-selectable build in Ra90 — 3-step (3000/4000/5000K) or 5-step (2700–5000K).

- Three sizes — 15W, 30W and 45W, delivering 1,500 to 4,250 lumens
- 10–60° zoomable beam — set the spread on site, no optic to change
- 350° rotation and 90° pivot
- Four fixed CCTs 2700K–5000K, or a 3-step / 5-step field-selectable build
- CREE COB source — Ra83 or Ra95 with fixed CCT, Ra90 with selectable CCT
- TRIAC or 0–10V dimming · power factor 0.95 · integral driver
- Fits 3-wire or 4-wire H-type track
- White or black



cETLus

CE

LUMEN OUTPUT	1,500 / 3,000 / 4,250 lm delivered (by size)
COLOR TEMP / CCT	2700 / 3000 / 4000 / 5000K fixed · 3CCT (3000/4000/5000K) · 5CCT (2700/3000/3500/4000/5000K)
CRI	83 / 95 (Ra) with fixed CCT · 90 (Ra) with selectable CCT
DISTRIBUTION	10–60° zoomable
LED SOURCE	CREE COB
WATTAGE	15 / 30 / 45W
VOLTAGE	120V · 100–277V

POWER FACTOR	0.95
DIMMING	TRIAC · 0–10V (non-dimming standard)
DRIVER	Integral, built into the head
FINISH	White, Black
MOUNTING	H-type track — 3-wire or 4-wire
DIMENSIONS	2.76" Ø × 6.10" L (70 × 155 mm) · 3.54" Ø × 7.52" L (90 × 191 mm) · 4.33" Ø × 8.46" L (110 × 215 mm)
WARRANTY	5-Year

FINISHES

WH
WhiteBK
Black

ORDERING


CONFIGURE YOUR PART NUMBER USING THE OPTIONS BELOW.

MODEL	WATTAGE	VOLTAGE	CCT	CRI	BEAM	CONTROLS	FINISH
PASCAL	15 15W 30 30W 45 45W	AC120 120V U 100-277V	27 2700K 30 3000K 40 4000K 50 5000K	83 Ra83 95 Ra95	Z0 10-60° zoomable	N Non-dimming (standard) TR TRIAC DV 0-10V	WH White BK Black
			3CCT (3000/4000/ 5000K) 5CCT (2700/3000/ 3500/4000/5000K)	90 Ra90			


Build Your Order Code — example values shown in grey

MODEL	WATTAGE	VOLTAGE	CCT	CRI	BEAM	CONTROLS	FINISH
PASCAL	30	U	3CCT	90	Z0	TR	WH

STANDARD FINISHES



WH
White



BK
Black

DIMENSIONS

WATTAGE	DIAMETER	LENGTH
15 15W	2.76" (70 mm)	6.10" (155 mm)
30 30W	3.54" (90 mm)	7.52" (191 mm)
45 45W	4.33" (110 mm)	8.46" (215 mm)

PERFORMANCE DATA

DELIVERED LUMENS BY SIZE

SIZE	DELIVERED LUMENS	EFFICACY
15W	1,500 lm	100 lm/W
30W	3,000 lm	100 lm/W
45W	4,250 lm	94 lm/W

The factory publishes one figure per size; output is not tabulated by CCT or CRI. Efficacy is derived from those figures. Measured at 25°C ambient; power factor 0.95.

Distribution 10-60° zoomable **Efficacy** — **IES File** On request