

W20 MAGNETIC TRACK LED SPOTLIGHT



INTRODUCTION

FEATURE

- Anti-glare Uniform Lighting UGR≤16
- Long Lifespan Design >50,000Hours
- Working Temperature: -20°C~40°C

MAIN MATERIAL

- LED BRAND: GUBO
- LED Driver Brand: GUBO
- Housing: Die-casted Aluminum
- Optics: High Efficiency PMMA Lens

INSTALLATION

- W20 Magnetic Track Slotted
- Suitable for Interior Lighting

STANDARD

- Designed and Manufactured to Comply with CE/RoHS/EMF/TUV/SAA/Erp/cETL/FCC
- IP20 Protection, Class III Electric

OPTION

- LED CCT: 1,800K~10,000K/R/G/B/Y
- [CRI]: Ra80, [G] Ra90, [H] RA97
- Custom Housing Finished Color:


Custom Housing Finished Color:

MATT WHITE [HMTWT]	MATT BLACK [HMTBK]
--------------------	--------------------

Custom Baffle Finished Color:

MATT WHITE [BFMTWT]	MATT BLACK [BFMTBK]
---------------------	---------------------

DIMENSION: [UNIT: MM]



CASE STUDY:



MODEL	POWER [W]	LED TYPE	CCT [K]	CRI	FLUX [LM]	POWER FACTOR	BEAM ANGLE	REMOTE CONTROL	INPUT [V]
GTR4423F	9W	9x2W SMD3030	G2700K	RA90	720	>0.5	BL24D:24°	[CDP]:PWM(1%) [REMOTE DRIVER] [CDT]:TRIAC(10%) [CDV]:0~10V(8%) [CDV0]:0~10V(1%) [CDV1]:1~10V(10%) [CDX]:DMX512(1%) [CDA]:DALI(1%) [CDZ]:ZIGBEE(1%) [CRF]:2.4GRF(1%)	DC24V [DC48V] [REMOTE DRIVER] AC220-240V [AC100-240V] [AC100-277V] [AC100-347V] 50/60Hz
			G3000K	RA90	810				
			G3500K	RA90	810				
			G4000K	RA90	855				
			G5000K	RA90	855				
			G6000K	RA90	810				
			H2700K	RA97	585				
			H3000K	RA97	630				
			H3500K	RA97	630				
			H4000K	RA97	675				
			H5000K	RA97	675				
			H6000K	RA97	630				
	2C@9W	9TGW	G2700K G6000K	RA90	585	>0.5			
GTR4423FF	9W	9x2W SMD3030	G2700K	RA90	720	>0.5	BDF: 120°	[CDP]:PWM(1%) [REMOTE DRIVER] [CDT]:TRIAC(10%) [CDV]:0~10V(8%) [CDV0]:0~10V(1%) [CDV1]:1~10V(10%) [CDX]:DMX512(1%) [CDA]:DALI(1%) [CDZ]:ZIGBEE(1%) [CRF]:2.4GRF(1%)	DC24V [DC48V] [REMOTE DRIVER] AC220-240V [AC100-240V] [AC100-277V] [AC100-347V] 50/60Hz
			G3000K	RA90	810				
			G3500K	RA90	810				
			G4000K	RA90	855				
			G5000K	RA90	855				
			G6000K	RA90	810				
			H2700K	RA97	585				
			H3000K	RA97	630				
			H3500K	RA97	630				
			H4000K	RA97	675				
			H5000K	RA97	675				
			H6000K	RA97	630				
	2C@9W	9TGW	G2700K G6000K	RA90	585	>0.5			

NOTE:

All parameters are measured at 25°C ambient temperature, 35% humidity experimental environment.

Tolerances of power and luminous flux are ±10%, tolerance of color rendering index is ±3.

CIP Lighting

T: 1-803-766-0243 W: www.ciplighting.com E: info@ciplighting.com