Bodo

Wall Step Light

A rectangular LED step light with a bevelled face — the frame chamfers back to a wide recessed slot, throwing a long low wash across a tread or path. The shallowest trim on the platform at 1.1″ deep, in two lengths, surface mounted on a wall, ceiling or 4″ J-box.

- Bevel face — chamfered frame around a wide recessed slot
- Rectangular only, two lengths — 6.7″ and 9.1″, both 3.2″ tall
- Output follows the length — 3W on 6.7″, 6W on 9.1″ (up to 410 lm)
- Shallowest trim on the platform — 1.1″ (28 mm) deep
- Anti-glare soft light · RA90 standard (RA80 / RA97 optional)



ETL FCC CE RoHS SAA IP65 IK08 Wet Location

LUMEN OUTPUT	180 – 410 lm (by length)
COLOR TEMP / CCT	2700K / 3000K / 3500K / 4000K / 5000K / 5700K / 6500K
CRI	RA90 (RA80 / RA97 optional)
BEAM ANGLE	T2M 65° × 135° · BDF 120° (LM-20%)
LED SOURCE	GUBO
WATTAGE	3W / 6W (by length)
VOLTAGE	AC 100–277V 50/60Hz · AC 220–240V · AC 110–130V · DC 12V / 24V / 36V / 42V
DIMMING	Non-dimmable standard · TRIAC / 0–10V / DALI / DMX512 / PWM · Zigbee / Bluetooth / 2.4G RF

DRIVER	GUBO
FINISH	White, Black, Grey, Dark Grey, Brass
IP / IMPACT	IP65 · IK08
MATERIAL	Die-cast aluminum housing · corrosion-resistant plastic sleeve
LENS	High-efficiency PC lens
MOUNTING	Wall or ceiling surface · [FJP] plate for 4″ J-box
DIMENSIONS	Rectangular 6.7″ × 3.2″ and 9.1″ × 3.2″ · 1.1″ deep
LIFETIME	>50,000 hrs

ORDERING

CONFIGURE YOUR PART NUMBER USING THE OPTIONS BELOW.

MODEL	SHAPE	SIZE	VOLTAGE	CCT	CRI	DIMMING	FINISH
BODO	RT Rectangular	67 6.7″ · 3W 91 9.1″ · 6W	U AC 100–277V AC220 AC 220–240V AC110 AC 110–130V DC12 DC 12V DC24 DC 24V DC36 DC 36V DC42 DC 42V	27 2700K 30 3000K 35 3500K 40 4000K 50 5000K 57 5700K 65 6500K TW Tunable White RGB RGBW RGBA	80 RA80 90 RA90 97 RA97	N Non-dimmable DT TRIAC DV 0–10V DA DALI DX DMX512 DP PWM ZB Zigbee BT Bluetooth RF 2.4G RF	WH White BK Black GY Grey AGY Dark Grey BR Brass

Build Your Order Code — example values shown in grey

MODEL	SHAPE	SIZE	VOLTAGE	CCT	CRI	DIMMING	FINISH
BODO	RT	67	U	30	90	N	BK

FINISHES

WH
White (RAL9010)

BK
Black (RAL9005)

GY
Grey (RAL7042)

AGY
Dark Grey (RAL7016)

BR
Brass (RAL1024)

BEVEL FACE — SIZES




67
6.7″ · 3W
170 × 81 mm



91
9.1″ · 6W
230 × 81 mm

DIMENSIONS

SHAPE	SIZE	FACE SIZE	OUTPUT
RT Rectangular	67	6.7″ × 3.2″ (170 × 81 mm)	3W
RT Rectangular	91	9.1″ × 3.2″ (230 × 81 mm)	6W
All	—	Depth 1.1″ (28 mm)	—



BEVEL-FACE TRIMS, RECTANGULAR ONLY — 6.7″ AND 9.1″ LONG, BOTH 3.2″ TALL. SIDE PROFILE AT LEFT — DEPTH IS 1.1″ (28 MM) ON BOTH SIZES.

PHOTOMETRY

DELIVERED LUMENS — WHITE, RA90

Optic	CCT	3W	6W
White (RA90)	2700K	180 lm	360 lm
	3000K	190 lm	380 lm
	3500K	190 lm	380 lm
	4000K	210 lm	410 lm
	5000K	210 lm	410 lm
	5700K	210 lm	410 lm
	6500K	200 lm	400 lm

Nominal delivered lumens at RA90; tolerance ±10% at 25°C. Output follows the length — 3W on size 67 (6.7″), 6W on size 91 (9.1″).

DELIVERED LUMENS — TUNABLE WHITE & COLOR

Mode	Output	3W	6W
TW Tunable White	Delivered	150 lm	320 lm
RGB	Delivered	120 lm	240 lm
RGBW	Delivered	150 lm	320 lm
RGBA	Delivered	120 lm	240 lm

Tunable White spans 2700K–6500K from one fixture. RGB / RGBW / RGBA are multi-chip (620 nm red · 520 nm green · 455 nm blue, plus 2700K white or amber); values are total delivered lumens with all channels at full.

BEAM ANGLE T2M 65° × 135° · BDF 120° (LM-20%) **EFFICACY** —