























| Series | | LED ROUND DRUM LIGHT SERIES | | | | | | | | Model | | DRUM | | | | | | |
|---|------------------|-----------------------------|-----------|-------|-----------------|--------------------------|--------|----------------|-----|---|---------------|---------------|-------------------|------------|------------------|---------------------|----------------|--|
|  | | | | | | | | | | Project: | | | | | | | | |
| | | | | | | | | | | Type: | | | | | | | | |
| | | | | | | | | | | Notes: | | | | | | | | |
| | | | | | | | | | | Overview | | | | | | | | |
| | | | | | | | | | | Introducing a luminaire with a classic shape and proportions, the round for general lighting applications. Available in multiple sizes, mountings, and light distributions to fit the scale, proportions and light output requirements of the project. Combining the elements of color, shape, and sound. ROUND acoustic is an extremely versatile lighting tool for a range of projects. Available in 4 sizes, adopt 0.35"(9mm) polyester fiber in a range of color options. With great acoustic performance, has sound absorbing, non-toxic, non-allergenic and non-irritant characteristics. | | | | | | | | |
| Certificate | | | | | | | | | | Features | | | | | | | | |
|    | | | | | | | | | | 1. Available in standard light, with acoustic 2. 2 standard color finishes: black, white, or aluminium body, other color can be customized. 3 Operation Voltage: AC120-277V, 0-10v dimming and non-dimmable for optional 4. Direct and indirect lighting for optional. 5. Efficiency: $\geq 85\text{lm/w}$ | | | | | | | | |
| Type | Suspended - Down | | | | | | | | | Size | | | | | | | | |
|  | | | | | | | | | | Model type | D | H | Direct Lumen/Watt | | Dimension Code | | | |
| | | | | | | | | | | DRUM-S-25W-AC | 18.9"(480mm) | 11.8"(300mm) | 2125/25W | | D19 | | | |
| | | | | | | | | | | DRUM-S-40W-AC | 23.6"(600mm) | 23.6"(600mm) | 3400/40W | | D24 | | | |
| | | | | | | | | | | DRUM-S-90W-AC | 35.4"(900mm) | 35.4"(900mm) | 7650/90W | | D35 | | | |
| | | | | | | | | | | DRUM-S-180W-AC | 47.2"(1200mm) | 47.2"(1200mm) | 15300/180W | | D47 | | | |
| | | | | | | | | | | | | | | | | | | |
| Discontinued Surface-mounted | | | | | | | | | | | | | | | | | | |
| Ordering Format | Model No. | Installation | | Power | | Acoustic Configuration | Height | | CRI | CCT | | Control | | Body Color | | Acoustic Color | Dimension Code | |
| | DRUM | S | Suspended | 25W | For size D18.9" | Blank - No acoustic | H12 | 11.8" (300mm) | 80+ | 30K | 3000K | STD | Non-dimming | SW | Matt white | Acoustic Color Code | D19 | |
| | | | | 40W | For size D23.6" | AC - Acoustic with light | H24 | 23.6" (600mm) | 90+ | 35K | 3500K | DIM | 0-10V dimming | SB | Matt black | | D24 | |
| | | | | 90W | For size D35.4" | | H35 | 35.4" (900mm) | | 40K | 4000K | | | RAL | Customized color | | D35 | |
| | | | | 180W | For size D47.2" | | H47 | 47.2" (1200mm) | | | | | | | | | D47 | |

PRODUCT SPECIFICATION

| | | | | | | | | |
|---------------------|---|---|---|---|---|--|---|---|
| Acoustic Color Code |  |  |  |  |  |  |  |  |
| |  |  |  |  |  |  |  |  |
| |  |  |  |  |  |  |  |  |
| |  |  |  |  |  |  |  |  |
| |  |  |  |  |  |  | | |
| Order Example: | DRUM-S-40W-AC-H12-80-30K-DIM--SW-NSAC-001 141-D19 | | | | | | | |

| Light distribution | Optical system |
|---|---|
|  |  <p>Beam Angle: 100.30°(50%Imax)</p> |

| Accessories |
|--|
| <div> <div> A.Mounting Bracket B.Anchor Screws C.Plastic Anchors D.Bracket Screws E.Canopy Screws F.Wire Connectors </div>  </div> |

| Material | LED system |
|---|---|
| LED Driver ARCATA or Equivalent, AC120-277V, PF>0.9, no flicker, UL Cert, Class P | LED Samsung 2835, 9V, 100mA |
| Alu PCB 2.0W.M/K, UL Cert | CCT 2700K, 3000K, 3500K, 4000K and 5000K with a great color consistency (within 6-step MacAdam ellipse) |
| Housing Alumium6063, painting. | Led life Minimum 50,000h with 70% of lumen maintenance in 25C ambient temperature, in compliance with IES LM-80 testing measurements. |
| Lens PC, UL-94VO, Anti-UV | Operation temp minus 20C to 40C (centigrade) |
| We reserve the right to make any design changes for continuous improvement without notification, contact us for the latest technical information! | File name |