

# **LED Track Light**

## **B** Series











## **North America**







#### **Main Features:**

- COB LED chips, no shadow, strong penetrability, high fidelity CRI 83/95 and high efficacy up to 110lm/W.
- Triac dimming, smooth range from 100% to 10%, and compatible with most dimmers, such as Lutron, Leviton, Smart Home, Arctic Lighting etc.
- UL certified driver, no flicker, high PF 0.98, instant start, noise free.
- Can point almost anywhere with 350 degree rotation and 90 degree pivot.
- Unique integrated built-in driver design, invisible wires, anti-glare.
- Compatible track systems: Halo, Juno, Lightolier and Global optional.
- 3 CCT adjustable (3000K, 4000K, 5000K) /5 CCT adjustable (2700K, 3000K, 3500K, 4000K, 5000K) optional.
- Finished color: Black, White and Silver grey optional.

|            |  |       | ,       | '                |   |                   |                 |         |
|------------|--|-------|---------|------------------|---|-------------------|-----------------|---------|
| Model No.  | Size                                   | Power | Voltage | Luminou<br>Flux  | s CCT<br>Optional                               | CRI               | Beam<br>Angle   | Dimming |
| CIP-TRB7W  | φ55xL93xH140mm<br>φ2.17"*L3.66"*H5.5"  | 7W    | AC120V  | 770lm<br>630lm   | 2700K/3000K/4000K/5000K<br>3CCT/5CCT adjustable | 83Ra/95Ra<br>90Ra | 15°/25°/36°/55° | Triac   |
| CIP-TRB10W | φ67xL110xH150mm<br>2.64"*L4.33"*H5.91" | 10W   | AC120V  | 1100lm<br>900lm  | 2700K/3000K/4000K/5000K<br>3CCT/5CCT adjustable | 83Ra/95Ra<br>90Ra | 15°/25°/36°/55° | Triac   |
| CIP-TRB15W | φ83xL115xH167mm<br>φ3.27"xL4.53"xH6.6" | 15W   | AC120V  | 1650lm<br>1350lm | 2700K/3000K/4000K/5000K<br>3CCT/5CCT adjustable | 83Ra/95Ra<br>90Ra | 15°/25°/36°/60° | Triac   |
| CIP-TRB20W | φ83xL115xH167mm<br>φ3.27"xL4.53"xH6.6" | 20W   | AC120V  | 2200lm<br>1800lm | 2700K/3000K/4000K/5000K<br>3CCT/5CCT adjustable | 83Ra/95Ra<br>90Ra | 15°/25°/36°/60° | Triac   |
| CIP-TRB25W | φ95xL133xH180mm<br>φ3.74"xL5.24"xH7.1" | 25W   | AC120V  | 2750lm<br>2250lm | 2700K/3000K/4000K/5000K<br>3CCT/5CCT adjustable | 83Ra/95Ra<br>90Ra | 12°/24°/36/60°  | Triac   |
| CIP-TRB30W | φ95xL133xH180mm<br>φ3.74"xL5.24"xH7.1" | 30W   | AC120V  | 3300lm<br>2700lm | 2700K/3000K/4000K/5000K<br>3CCT/5CCT adjustable | 83Ra/95Ra<br>90Ra | 12°/24°/36°/60° | Triac   |

Remark: Single CCT Luminous flux is based on 3000K, 83Ra, 36°, 3/5 CCT Luminous flux is based on 3000K, 90Ra, 36°.

### **Applications:**

- Clothing/Shoe/Furniture/Jewelry stores
- Supermarkets
- Hotels/ Restaurant
- Auto shops
- Museum/Gallery

