




FEATURES:

- Aluminum body
- Poly carbonate Cover
- Replaceable LED strips
- Isolated LED driver
- Easy maintenance

OPTIONS:

- Dimmable: TRIAC, 0/1-10V, DALI
- Color: White, Silver, Black



MODEL NO.	WATTAGE	DIMENSION L * W * H(mm)	VOLTAGE	COLOR	CRI	LUMENS	BEAM ANGLE	WARRANTY
CIP-LED10-SOPC(F)	10W	579x51x65	100-277V 120-347V 220-240V	3000K 4000K 5000K 6500K	CRI>83 CRI>90	115Lm/W 140Lm/W	120°	5 years
CIP-LED20-SOPC(F)	20W	1189x51x65						
CIP-LED30-SOPC(F)	30W	1189x51x65						
CIP-LED40-SOPC(F)	40W	1189x51x65						
CIP-LED25-SOPC(F)	25W	1475x51x65						
CIP-LED30-SOPC(F)	30W	1475x51x65						
CIP-LED50-SOPC(F)	50W	1475x51x65						
CIP-LED60-SOPC(F)	60W	1475x51x65						
CIP-LED40-SOPC(F)	40W	2369x51x65						
CIP-LED80-SOPC(F)	80W	2369x51x65						




FEATURES:

- Aluminum Body
- Poly carbonate Cover
- Replaceable LED strips
- Isolated LED driver
- Easy maintenance

OPTIONS:

- Dimmable: TRIAC, 0/1-10V, DALI
- Color: White, Silver, Black



MODEL NO.	WATTAGE	DIMENSION L * W * H(mm)	VOLTAGE	COLOR	CRI	LUMENS	BEAM ANGLE	WARRANTY
CIP-LED10-SOPC(FS)	10W	579x51x65	100-277V 120-347V 220-240V	3000K 4000K 5000K 6500K	CRI>83 CRI>90	115Lm/W 140Lm/W	120°	5 years
CIP-LED20-SOPC(FS)	20W	1189x51x65						
CIP-LED30-SOPC(FS)	30W	1189x51x65						
CIP-LED40-SOPC(FS)	40W	1189x51x65						
CIP-LED25-SOPC(FS)	25W	1475x51x65						
CIP-LED30-SOPC(FS)	30W	1475x51x65						
CIP-LED50-SOPC(FS)	50W	1475x51x65						
CIP-LED60-SOPC(FS)	60W	1475x51x65						
CIP-LED40-SOPC(FS)	40W	2369x51x65						
CIP-LED80-SOPC(FS)	80W	2369x51x65						




FEATURES:

- Aluminum Body
- Poly carbonate Cover
- Replaceable LED strips
- Isolated LED driver
- Easy maintenance

OPTIONS:

- Dimmable: TRIAC, 0/1-10V, DALI
- Color: White, Silver, Black



MODEL NO.	WATTAGE	DIMENSION L*W*H(mm)	VOLTAGE	COLOR	CRI	LUMENS	BEAM ANGLE	WARRANTY
CIP-LED10-SOPC	10W	579x51x65	100-277V 120-347V 220-240V	3000K 4000K 5000K 6500K	CRI>83 CRI>90	115Lm/W 140Lm/W	120°	5 years
CIP-LED20-SOPC	20W	1189x51x65						
CIP-LED30-SOPC	30W	1189x51x65						
CIP-LED40-SOPC	40W	1189x51x65						
CIP-LED25-SOPC	25W	1474x51x65						
CIP-LED30-SOPC	30W	1474x51x65						
CIP-LED50-SOPC	50W	1474x51x65						
CIP-LED60-SOPC	60W	1474x51x65						
CIP-LED40-SOPC	40W	2369x51x65						
CIP-LED80-SOPC	80W	2369x51x65						




FEATURES:

- Aluminum Body
- Poly carbonate Cover
- Replaceable LED strips
- Isolated LED driver
- Easy maintenance

OPTIONS:

- Dimmable: TRIAC, 0/1-10V, DALI
- Microwave motion sensor
- Emergency battery back up
- Color: White, Silver, Black



MODEL NO.	WATTAGE	DIMENSION L*W*H(mm)	VOLTAGE	COLOR	CRI	LUMENS	BEAM ANGLE	WARRANTY
CIP-LED220-SOPC(S)	40W	1188x83x92	100-277V 120-347V 220-240V	3000K 4000K 5000K 6500K	CRI>83 CRI>90	115Lm/W 140Lm/W	120°	5 years
CIP-LED320-SOPC(S)	60W	1188x83x92						
CIP-LED225-SOPC(S)	50W	1474x83x92						
CIP-LED230-SOPC(S)	60W	1474x83x92						
CIP-LED245-SOPC(S)	90W	1474x83x92						
CIP-LED250-SOPC(S)	100W	1474x83x92						
CIP-LED240-SOPC(S)	80W	2372x83x92						
CIP-LED260-SOPC(S)	120W	2372x83x92						
CIP-LED440-SOPC(S)	160W	2372x83x92						




FEATURES:

- Aluminum Body
- Poly carbonate Cover + Plastic Louver
- Replaceable LED strips
- Built-in LED driver
- Easy maintenance

OPTIONS:

- Dimmable: TRIAC, 0/1-10V, DALI
- Color: White, Silver, Black
- 3-CCT turnable
- Wattage switchable
- Bluetooth remote control



MODEL NO.	WATTAGE	DIMENSION L * W * H(mm)	VOLTAGE	COLOR	CRI	LUMENS	BEAM ANGLE	WARRANTY
CIP-LED10-SOPC(G)	10W	565x49x64	100-277V 120-347V 220-240V	3000K 4000K 5000K 6500K	CRI>83 CRI>90	115Lm/W 140Lm/W	120°	5 years
CIP-LED20-SOPC(G)	20W	1125x49x64						
CIP-LED30-SOPC(G)	30W	1125x49x64						
CIP-LED40-SOPC(G)	40W	1125x49x64						
CIP-LED25-SOPC(G)	25W	1405x49x64						
CIP-LED30-SOPC(G)	30W	1405x49x64						
CIP-LED50-SOPC(G)	50W	1405x49x64						
CIP-LED60-SOPC(G)	60W	1405x49x64						
CIP-LED40-SOPC(G)	40W	2245x49x64						
CIP-LED80-SOPC(G)	80W	2245x49x64						




FEATURES:

- Aluminum Body
- Plastic Reflector
- Replaceable LED strips
- Built-in LED driver
- Easy maintenance

OPTIONS:

- Dimmable: TRIAC, 0/1-10V, DALI
- Color: White, Silver, Black
- Wattage switchable
- Bluetooth remote control



MODEL NO.	WATTAGE	DIMENSION L * W * H(mm)	VOLTAGE	COLOR	CRI	LUMENS	BEAM ANGLE	WARRANTY
CIP-LED10-SOPC(S)	10W	576x49x64	100-277V 120-347V 220-240V	3000K 4000K 5000K 6500K	CRI>83 CRI>90	115Lm/W 140Lm/W	120°	5 years
CIP-LED20-SOPC(S)	20W	1147x49x64						
CIP-LED30-SOPC(S)	30W	1147x49x64						
CIP-LED40-SOPC(S)	40W	1147x49x64						
CIP-LED25-SOPC(S)	25W	1434x49x64						
CIP-LED30-SOPC(S)	30W	1434x49x64						
CIP-LED50-SOPC(S)	50W	1434x49x64						
CIP-LED60-SOPC(S)	60W	1434x49x64						
CIP-LED40-SOPC(S)	40W	2292x49x64						
CIP-LED80-SOPC(S)	80W	2292x49x64						