


Min Bending Diameter



Cross Section(mm)

Cable Option

Integrated End Cap (IP68)



Front Entry




Bottom Entry





Closed End Cap


Accessories





Aluminium Profile
(1m/2m/3m)




Aluminium Mounting Clips
(2cm)





Flexible Profile
(1m)



PC Profile
(1m/2m/3m)



PC Profile
(1m/2m/3m)



PC Mounting Clips
(2cm)

Single Color

CIP - 2835 N P V W 8 - 16x17mm 10W - 14024 - W/R/G/B/Y/O/P
CIP - 2835 N P V W 8 - 16x17mm 10W - 12024C - W/R/G/B/Y/O/P

CCT		Power(W)	Efficiency (LM/W)	Lumen (LM/M)	Cutting Unit (mm)	Max. Run Length (M)
1800K	CV	10	49.4	494	50	8
	CC	10	42.3	423	50	14
2100K	CV	10	54.8	548	50	8
	CC	10	47	470	50	14
2400K	CV	10	59.3	593	50	8
	CC	10	50.8	508	50	14
2700K	CV	10	62.2	622	50	8
	CC	10	53.3	533	50	14
3000K	CV	10	63.9	639	50	8
	CC	10	54.8	548	50	14
3500K	CV	10	63.7	637	50	8
	CC	10	54.6	546	50	14
4000K	CV	10	72.1	721	50	8
	CC	10	61.8	618	50	14
5000K	CV	10	66.9	669	50	8
	CC	10	57.3	573	50	14
6500K	CV	10	64.7	647	50	8
	CC	10	55.5	555	50	14
Red	CV	10	29	290	50	10
	CC	10	24.9	249	50	19
Green	CV	10	72.1	721	50	7
	CC	10	61.8	618	50	12
Blue	CV	10	15	150	50	8
	CC	10	12.9	129	50	14
Yellow	CV	10	22.1	221	50	10
	CC	10	19	190	50	19
Orange	CV	10	26.4	264	50	10
	CC	10	22.6	226	50	19
Pink	CV	10	60.7	607	50	8
	CC	10	52	520	50	14

CCT Tunable

CIP - 2835 N P V W 8 - 16x17mm 15W - 19224 - (27-65K)

CCT	Power(W)	Efficiency (LM/W)	Lumen (LM/M)	Cutting Unit (mm)	Max. Run Length (M)
2700K	7.5	56.7	425	62.5	5
6000K	7.5	59.3	445	62.5	5
2700K+6000K	15	57.5	863	62.5	5

RGB**CIP - 5050 N P V W 8 - 16x17mm 10W - 9624 - RGB**

CCT	Power(W)	Efficiency (LM/W)	Lumen (LM/M)	Cutting Unit (mm)	Max. Run Length (M)
R	3.3	19.6	65	62.5	5
G	3.3	57.9	191	62.5	5
B	3.3	12.9	43	62.5	5
RGB	10	30.8	308	62.5	5

RGBW**CIP - 5060 N P V W 8 - 16x17mm 15W - 9624 - RGBW**

CCT	Power(W)	Efficiency (LM/W)	Lumen (LM/M)	Cutting Unit (mm)	Max. Run Length (M)
R	3.7	20.2	76	62.5	5
G	3.7	48.8	183	62.5	5
B	3.7	15.6	59	62.5	5
W(3000K)	3.7	57.4	215	62.5	5
RGBW	15	34.6	519	62.5	5

RGBW Pixel**CIP - 5060 N P V W 8 - 16x17mm 15W - 8024I - RGBW**

CCT	Power(W)	Efficiency (LM/W)	Lumen (LM/M)	Cutting Unit (mm)	Max. Run Length (M)	Protocol
R	5	8.4	42	125	7	DMX512
G	5	21.1	106	125	7	
B	5	5.9	30	125	7	
W(4000K)	5	28.3	142	125	7	
RGBW	15	20.4	306	125	7	

Note: CV=Constant Voltage CC=Constant Current