




**FEATURES:**

- Aluminum Body
- Poly carbonate Cover
- Replaceable LED strips
- Isolated LED driver
- Easy maintenance

**OPTIONS:**

- Dimmable: TRIAC, 0/1-10V, DALI
- Color: White, Silver, Black



MODEL NO.	WATTAGE	DIMENSION L * W * H(mm)	VOLTAGE	COLOR	CRI	LUMENS	BEAM ANGLE	WARRANTY
CIP-LED210-JLPC	20W	594x86x65	100-277V 120-347V 220-240V	3000K 4000K 5000K 6500K	CRI>83 CRI>90	115Lm/W 140Lm/W	120°	5 years
CIP-LED220-JLPC	40W	1204x86x65						
CIP-LED320-JLPC	60W	1204x86x65						
CIP-LED224-JLPC	50W	1490x86x65						
CIP-LED230-JLPC	60W	1490x86x65						
CIP-LED240-JLPC	80W	2374x86x65						
CIP-LED245-JLPC	90W	1490x86x65						
CIP-LED250-JLPC	100W	1490x86x65						
CIP-LED260-JLPC	120W	2374x86x65						




**FEATURES:**

- Aluminum body
- Poly carbonate Cover
- Replaceable LED strips
- Isolated LED driver
- Easy maintenance

**OPTIONS:**

- Dimmable: TRIAC, 0/1-10V, DALI
- Color: White, Silver, Black



MODEL NO.	WATTAGE	DIMENSION L * W * H(mm)	VOLTAGE	COLOR	CRI	LUMENS	BEAM ANGLE	WARRANTY
CIP-LED210-JLPC(2)	20W	574x66x75	100-277V 120-347V 220-240V	3000K 4000K 5000K 6500K	CRI>83 CRI>90	115Lm/W 140Lm/W	120°	5 years
CIP-LED220-JLPC(2)	40W	1184x66x75						
CIP-LED320-JLPC(2)	60W	1184x66x75						
CIP-LED224-JLPC(2)	50W	1470x66x75						
CIP-LED230-JLPC(2)	60W	1470x66x75						
CIP-LED240-JLPC(2)	80W	2364x66x75						
CIP-LED245-JLPC(2)	90W	1470x66x75						
CIP-LED250-JLPC(2)	100W	1470x66x75						
CIP-LED260-JLPC(2)	120W	2364x66x75						




**FEATURES:**

- Aluminum body
- Poly carbonate Cover
- Replaceable LED strips
- Isolated LED driver
- Easy maintenance

**OPTIONS:**

- Dimmable: TRIAC, 0/1-10V, DALI
- Color: White, Silver, Black




**FEATURES:**

- Aluminum Body
- Poly carbonate Cover
- Replaceable LED strips
- Isolated LED driver
- Easy maintenance

**OPTIONS:**

- Dimmable: TRIAC, 0/1-10V, DALI
- Color: White, Silver, Black



MODEL NO.	WATTAGE	DIMENSION L * W * H(mm)	VOLTAGE	COLOR	CRI	LUMENS	BEAM ANGLE	WARRANTY
CIP-LED210-JLPC(3)	20W	578x66x83	100-277V 120-347V 220-240V	3000K 4000K 5000K 6500K	CRI>83 CRI>90	115Lm/W 140Lm/W	120°	5 years
CIP-LED220-JLPC(3)	40W	1188x66x83						
CIP-LED320-JLPC(3)	60W	1188x66x83						
CIP-LED224-JLPC(3)	50W	1474x66x83						
CIP-LED230-JLPC(3)	60W	1474x66x83						
CIP-LED240-JLPC(3)	80W	2369x66x83						
CIP-LED245-JLPC(3)	90W	1474x66x83						
CIP-LED250-JLPC(3)	100W	1474x66x83						
CIP-LED260-JLPC(3)	120W	2369x66x83						

MODEL NO.	WATTAGE	DIMENSION L * W * H(mm)	VOLTAGE	COLOR	CRI	LUMENS	BEAM ANGLE	WARRANTY
CIP-LED210-JLPC(S)	20W	594x86x65	100-277V 120-347V 220-240V	3000K 4000K 5000K 6500K	CRI>83 CRI>90	115Lm/W 140Lm/W	120°	5 years
CIP-LED220-JLPC(S)	40W	1204x86x65						
CIP-LED230-JLPC(S)	60W	1204x86x65						
CIP-LED224-JLPC(S)	50W	1490x86x65						
CIP-LED230-JLPC(S)	60W	1490x86x65						
CIP-LED245-JLPC(S)	90W	1490x86x65						
CIP-LED250-JLPC(S)	100W	1490x86x65						
CIP-LED240-JLPC(S)	80W	2374x86x65						
CIP-LED260-JLPC(S)	120W	2374x86x65						




**FEATURES:**

- Aluminum body
- Poly carbonate Cover
- Replaceable LED strips
- Isolated LED driver
- 120° beam angle
- Easy maintenance

**OPTIONS:**

- Dimmable: TRIAC, 0/1-10V, DALI
- Color: White, Silver, Black



MODEL NO.	WATTAGE	DIMENSION L * W * H(mm)	VOLTAGE	COLOR	CRI	LUMENS	BEAM ANGLE	WARRANTY
CIP-LED210-JLPC (2S)	20W	574x66x75	100-277V 120-347V 220-240V	3000K 4000K 5000K 6500K	CRI>83 CRI>90	115Lm/W 140Lm/W	120°	5 years
CIP-LED220-JLPC(2S)	40W	1184x66x75						
CIP-LED230-JLPC(2S)	60W	1184x66x75						
CIP-LED224-JLPC(2S)	50W	1470x66x75						
CIP-LED230-JLPC(2)S	60W	1470x66x75						
CIP-LED245-JLPC(2S)	90W	1470x66x75						
CIP-LED250-JLPC(2S)	100W	1470x66x75						
CIP-LED240-JLPC(2)S	80W	2364x66x75						
CIP-LED260-JLPC(2S)	120W	2364x66x75						