


GTR6721A-MC90A: LED TUBULAR LIGHT

INTRODUCTION



FEATURE

Creative Innovation of Optimized LED Technology
 Skilled Manufacturing to Keep Durable Uniform Quality
 Long Lifespan Design >50,000hours
 Working Temperature: -20°C~50°C

MATERIAL & FINISH

LED Brand: GUBO [LM80]
 Remote Flicker-free Driver Brand: GUBO
 Profile: Aluminum Radiator Profile
 Optics: High Efficiency Opal PC Diffuser

INSTALLATION

Installation: Suspended or Surface Mounted By Clips
 Suitable for Interior Ceiling Light, like Office.....

STANDARD

Designed and Manufactured to Comply with
 TUV/CB/CE/RoHS/EMF/SAA/Erp/UL/cUL/FCC/SA
 SO

IP20 Protection, Class III Electric
(MCB)&(MCB): Waterproof Protection IP65

OPTION

LED CCT: 1,800K~10,000K/R/G/B/Y
 [CRI]: [E] RA80, [G] RA90, [H] RA97
 Custom Housing Finish Color: (RAL Code)

WHITE RAL9010P	BLACK RAL9005P	GREY RAL7042P	DARK GREY RAL7016P	BRASS RAL1024P
--------------------------	--------------------------	-------------------------	------------------------------	--------------------------

Horizontal Wire Pendant
 (MCA90HA) IP20
 (MCB90HA) IP65

Vertical Pendant
 (MCA90VA) IP20
 (MCB90VA) IP65

(MCC90VA) IP20
 (MCD90VA) IP65
 Downward Light



CIRCULAR CANOPY: LED DRIVE PLACEABLE							
MODEL:	CC120H50A	CC150H50A	CC200H50A	CC250H50A	CE250H40A	CE350H40A	CE500H50A
IMAGE							
DIMENSION(MM)	Φ125xH40	Φ125xH40	S125xH40	Φ250xH50	Φ250xH40	Φ350xH40	Φ500xH50
APPLICATION:	UP TO 30W	UP TO 60W	UP TO 120W	UP TO 240W	UP TO 150W	UP TO 300W	UP TO 800W

JBOX MOUNTING PLATE ON 4" OCTAGON JBOX			RECTANGLE CANOPY: LED DRIVE PLACEABLE				
MODEL:	FJP-C125A	FJP-C125B	FJP-S125A	RE305A	RE610A	RE915A	RE1220A
IMAGE							
DIMENSION(MM)	Φ125xH4	Φ125xH4	S125xH4	D305xW140xH40	D610xW140xH40	D915xW140xH40	D1220xW140xH40
APPLICATION:				UP TO 200W	UP TO 400W	UP TO 600W	UP TO 800W

[FPW] PENDANT	[FWA] WALL MOUNT	[FWB] WALL MOUNT	[FWC] WALL MOUNT
DIMENSION(MM)	[FWA]	[FWB] REMOTE DRIVER	[FWC]
 Φ90/3.54" L305/12" L610/24" L915/36" L1000/39.4" L1220/48" L1525/60" L1830/72" L2000/78.8" L2440/96"	 (≤L610mm): 150/5.9" (≤L1220mm): 250/9.9" 125/4.9" Length	 30/1.2" 125/5" Length	 (≤L1220mm): 150/5.9" (≤L2440mm): 250/9.9" 160 Length

CASE STUDY: (MCB) VERTICAL PENDANT

CASE STUDY: (MCA) HORIZONTAL PENDANT



GTR6721A-MC90A: LED TUBULAR LIGHT

INTRODUCTION

MODEL	POWER [W]	LED TYPE	CCT [K]			CRI	LUMEN [LM]	POWER FACTOR	BEAM ANGLE	OPTIONAL DIMMING	INPUT [V]
GTR6721A-MCA90HA (IP20) MCA90VA (IP20) MCC90VA (IP20) MCB90HA (IP65) MCB90VA (IP65) MCD90VA (IP65) -L305	15W [12W] [LDW]:6W	120x0.5W SMD2835	H2700K			RA97	1220	> 0.9	360°		
			H3000K			RA97	1320				
			H3500K			RA97	1320				
			H4000K			RA97	1420				
			H5000K			RA97	1420				
			H6000K			RA97	1420				
	2C@15W	TWH	H2700K	H6000K		RA97	1000	> 0.7			
4C@15W	RGBW	620nm	520nm	465nm	H2700K	\	1000	> 0.6			
5C@15W	RGBTW	620nm	520nm	465nm	H2700K	H6000K	\	1000	> 0.4		
GTR6721A-MCA90HA (IP20) MCA90VA (IP20) MCC90VA (IP20) MCB90HA (IP65) MCB90VA (IP65) MCD90VA (IP65) -L610	30W [25W] [20W] [LDW]:6W	240x0.5W SMD2835	H2700K			RA97	2460	> 0.9	360°		
			H3000K			RA97	2640				
			H3500K			RA97	2640				
			H4000K			RA97	2830				
			H5000K			RA97	2830				
			H6000K			RA97	2830				
	2C@30W	TWH	H2700K	H6000K		RA97	2000	> 0.9			
4C@30W	RGBW	620nm	520nm	465nm	H2700K	\	2000	> 0.7			
5C@30W	RGBTW	620nm	520nm	465nm	H2700K	H6000K	\	2000	> 0.5		
GTR6721A-MCA90HA (IP20) MCA90VA (IP20) MCC90VA (IP20) MCB90HA (IP65) MCB90VA (IP65) MCD90VA (IP65) -L915	45W [40W] [30W] [LDW]:6W	360x0.5W SMD2835	H2700K			RA97	3380	> 0.9	360°		
			H3000K			RA97	3960				
			H3500K			RA97	3960				
			H4000K			RA97	4250				
			H5000K			RA97	4250				
			H6000K			RA97	4250				
	2C@45W	TWH	H2700K	H6000K		RA97	3000	> 0.9			
4C@45W	RGBW	620nm	520nm	465nm	H2700K	\	3000	> 0.7			
5C@45W	RGBTW	620nm	520nm	465nm	H2700K	H6000K	\	3000	> 0.6		
GTR6721A-MCA90HA (IP20) MCA90VA (IP20) MCC90VA (IP20) MCB90HA (IP65) MCB90VA (IP65) MCD90VA (IP65) -L1000	50W [40W] [30W] [LDW]:6W	420x0.5W SMD2835	H2700K			RA97	4100	> 0.9	360°		
			H3000K			RA97	4400				
			H3500K			RA97	4400				
			H4000K			RA97	4720				
			H5000K			RA97	4720				
			H6000K			RA97	4720				
	2C@50W	TWH	H2700K	H6000K		RA97	3330	> 0.9			
4C@50W	RGBW	620nm	520nm	465nm	H2700K	\	3330	> 0.7			
5C@50W	RGBTW	620nm	520nm	465nm	H2700K	H6000K	\	3330	> 0.5		
GTR6721A-MCA90HA (IP20) MCA90VA (IP20) MCC90VA (IP20) MCB90HA (IP65) MCB90VA (IP65) MCD90VA (IP65) -L1220	60W [75W] [50W] [LDW]:6W	480x0.5W SMD2835	H2700K			RA97	4910	> 0.9	360°		
			H3000K			RA97	5280				
			H3500K			RA97	5280				
			H4000K			RA97	5660				
			H5000K			RA97	5660				
			H6000K			RA97	5660				
	2C@60W	TWH	H2700K	H6000K		RA97	4000	> 0.9			
4C@60W	RGBW	620nm	520nm	465nm	H2700K	\	4000	> 0.7			
5C@60W	RGBTW	620nm	520nm	465nm	H2700K	H6000K	\	4000	> 0.5		
GTR6721A-MCA90HA (IP20) MCA90VA (IP20) MCC90VA (IP20) MCB90HA (IP65) MCB90VA (IP65) MCD90VA (IP65) -L1525	75W [60W] [50W] [LDW]:6W	600x0.5W SMD2835	H2700K			RA97	6130	> 0.9	360°		
			H3000K			RA97	6600				
			H3500K			RA97	6600				
			H4000K			RA97	7080				
			H5000K			RA97	7080				
			H6000K			RA97	7080				
	2C@75W	TWH	H2700K	H6000K		RA97	5000	> 0.9			
4C@75W	RGBW	620nm	520nm	465nm	H2700K	\	5000	> 0.7			
5C@75W	RGBTW	620nm	520nm	465nm	H2700K	H6000K	\	5000	> 0.5		
GTR6721A-MCA90HA (IP20) MCA90VA (IP20) MCC90VA (IP20) MCB90HA (IP65) MCB90VA (IP65) MCD90VA (IP65) -L1830	90W [80W] [60W] [LDW]:6W	720x0.5W SMD2835	H2700K			RA97	7350	> 0.9	360°		
			H3000K			RA97	7920				
			H3500K			RA97	7920				
			H4000K			RA97	8500				
			H5000K			RA97	8500				
			H6000K			RA97	8500				
	2C@90W	TWH	H2700K	H6000K		RA97	6000	> 0.9			
4C@90W	RGBW	620nm	520nm	465nm	H2700K	\	6000	> 0.7			
5C@90W	RGBTW	620nm	520nm	465nm	H2700K	H6000K	\	6000	> 0.6		
GTR6721A-MCA90HA (IP20) MCA90VA (IP20) MCC90VA (IP20) MCB90HA (IP65) MCB90VA (IP65) MCD90VA (IP65) -L2000	100W [80W] [60W] [LDW]:6W	840x0.5W SMD2835	H2700K			RA97	8180	> 0.9	360°		
			H3000K			RA97	8800				
			H3500K			RA97	8800				
			H4000K			RA97	9430				
			H5000K			RA97	9430				
			H6000K			RA97	9430				
	2C@100W	TWH	H2700K	H6000K		RA97	6660	> 0.9			
4C@100W	RGBW	620nm	520nm	465nm	H2700K	\	6660	> 0.7			
5C@100W	RGBTW	620nm	520nm	465nm	H2700K	H6000K	\	6660	> 0.5		
GTR6721A-MCA90HA (IP20) MCA90VA (IP20) MCC90VA (IP20) MCB90HA (IP65) MCB90VA (IP65) MCD90VA (IP65) -L2440	120W [100W] [80W] [LDW]:6W	960x0.5W SMD2835	H2700K			RA97	9820	> 0.9	360°		
			H3000K			RA97	10560				
			H3500K			RA97	10560				
			H4000K			RA97	11320				
			H5000K			RA97	11320				
			H6000K			RA97	11320				
	2C@120W	TWH	H2700K	H6000K		RA97	8000	> 0.9			
4C@120W	RGBW	620nm	520nm	465nm	H2700K	\	8000	> 0.7			
5C@120W	RGBTW	620nm	520nm	465nm	H2700K	H6000K	\	8000	> 0.6		

NOTE:

All parameters are measured at 25°C ambient temperature, 35% humidity experimental environment. Tolerances of power and luminous flux are ±10%, tolerance of color rendering index is ±3.