

# INTRODUCTION

# RATTAN LIGHTING FIXTURE

### FEATURE

Elegance Design with Durable Quality  
 Long Lifespan Design >50,000hours  
 Working Temperature: -30°C~50°C

### MATERIALS & FINISH

Frame: Galvanized Steel  
 Shade: Environment-friendly Rattan  
 Lamp Holder: E26 Fitment

### INSTALLATION

According to models choosing.

### STANDARD

Designed and Manufactured to Comply with  
 TUV/CE/ROHS/GS/cUL Standard  
 IP20 Protection, Class I Electrical

### OPTION

LED Color Temperature: CCT2700~6000K  
 LED Lamp: E26 (MAXI.50W)

100-277V

RGBW

3 YEARS WARRANTY

360°

IP65

EURO

USA.CA

Ceiling (451F)	Pendant (551F)	Catenary (551FB)	Wall Mounted (611F)
<p>Φ 12 cm / 4.72"</p> <p>h 22.50 cm / 8.86"</p> <p>Φ 27 cm / 10.63"</p>	<p>Φ 12 cm / 4.72"</p> <p>h 200 cm / 78.74"</p> <p>Φ 27 cm / 10.63"</p>	<p>Φ 12 cm / 4.72"</p> <p>h 18 cm / 6.30"</p> <p>Φ 27 cm / 10.63"</p>	<p>Φ 12 cm / 4.72"</p> <p>h 28 cm / 10.24"</p> <p>Φ 27 cm / 10.63"</p>

  

Custom Lamp Shade Color Finish:	(451)	711F-L36CM	Floor																			
WHITE			711L-L61CM																			
COFFEE			711L-L132CM																			
BLACK																						
	<p>Φ 120</p> <p>F: 225/6.86"</p> <p>H: 330/13"</p> <p>L: 580/22"</p>	<p>Φ 27 cm / 10.63"</p>	<p>h 35.50 cm / 13.98"</p> <p>Φ 14 cm / 5.51"</p> <p>390 cm / 153.54"</p>																			
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>MATT WHITE [HMWT]</th> <th>MATT BLACK [HMBK]</th> <th>MATT SILVER [HMSV]</th> <th>MATT BRASS [HMBR]</th> <th>MATT GOLDEN [HMGD]</th> </tr> </thead> <tbody> <tr> <td style="background-color: white;"></td> <td style="background-color: black;"></td> <td style="background-color: silver;"></td> <td style="background-color: gold;"></td> <td style="background-color: yellow;"></td> </tr> </tbody> </table>	MATT WHITE [HMWT]	MATT BLACK [HMBK]	MATT SILVER [HMSV]	MATT BRASS [HMBR]	MATT GOLDEN [HMGD]						<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>GLOSSY CHROME [HGCM]</th> <th>GLOSSY NICKEL [HGBK]</th> <th>GLOSSY BRASS [HGBR]</th> <th>BRUSHED BRASS [HGBS]</th> <th>BRUSHED BRONZE [HGBZ]</th> </tr> </thead> <tbody> <tr> <td style="background-color: chrome;"></td> <td style="background-color: nickel;"></td> <td style="background-color: brass;"></td> <td style="background-color: brushed-brass;"></td> <td style="background-color: brushed-bronze;"></td> </tr> </tbody> </table>	GLOSSY CHROME [HGCM]	GLOSSY NICKEL [HGBK]	GLOSSY BRASS [HGBR]	BRUSHED BRASS [HGBS]	BRUSHED BRONZE [HGBZ]						<p>h 72 cm / 28.35"</p> <p>Φ 72 cm / 28.35"</p> <p>300 cm / 119.61"</p> <p>Φ 14 cm / 5.51"</p>
MATT WHITE [HMWT]	MATT BLACK [HMBK]	MATT SILVER [HMSV]	MATT BRASS [HMBR]	MATT GOLDEN [HMGD]																		
GLOSSY CHROME [HGCM]	GLOSSY NICKEL [HGBK]	GLOSSY BRASS [HGBR]	BRUSHED BRASS [HGBS]	BRUSHED BRONZE [HGBZ]																		

### CASE STUDY:



MODEL	NAME	INPUT [V]	FITMENT		DIEMENSION [INCH]	SHADE FINISH	BODY FINISH
			TYPE	POWER			
GTF5801-451F	CEILING	AC100~277V	1xE26	Maxi.1x50W	Dia.10.6" x H8.9"		
GTF5801-451H	CEILING	AC100~277V	1xE26	Maxi.1x50W	Dia.15.74" x H13"		
GTF5801-451K	CEILING	AC100~277V	1xE26	Maxi.1x50W	Dia.23.6" x H19"		
GTF5801-451L	CEILING	AC100~277V	1xE26	Maxi.1x50W	Dia.28.35" x H22"		
GTF5801-551F	Pendant	AC100~277V	1xE26	Maxi.1x50W	Dia.10.6" x H78.8"		
GTF5801-551H	Pendant	AC100~277V	1xE26	Maxi.1x50W	Dia.15.74" x H83"		
GTF5801-551K	Pendant	AC100~277V	1xE26	Maxi.1x50W	Dia.23.6" x H90"		
GTF5801-551L	Pendant	AC100~277V	1xE26	Maxi.1x50W	Dia.28.35" x H93"		
GTF5801-551FB	Catenary	AC100~277V	1xE26	Maxi.1x50W	Dia.10.6" x H137.8"		
GTF5801-611F	Wall	AC100~277V	1xE26	Maxi.1x50W	Dia.10.6" x H12.8"		
GTF5801-711F-L36CM	Floor	AC100~277V	1xE26	Maxi.1x50W	Dia.10.6" x H14"		
GTF5801-711L-L61CM	Floor	AC100~277V 50/60Hz	1xE26	Maxi.1x50W	Dia.28.35" x H24"		
GTF5801-711L-L132CM	Floor	AC100~277V 50/60Hz	1xE26	Maxi.1x50W	Dia.28.35" x H52.3"		

### NOTE:

All parameters are measured at 25°C ambient temperature, 35% humidity experimental environment.  
 Tolerances of power and luminous flux are ±10%, tolerance of color rendering index is ±5.

CIP Lighting

T: 1-803-766-0243

W: [www.ciplighting.com](http://www.ciplighting.com)

E: [info@ciplighting.com](mailto:info@ciplighting.com)